

Shamrock Foods 850 Purchase Order

X12/V5010/850: 850 Purchase Order

Author:	SPS Commerce
Company:	Shamrock Foods
Notes:	

850 Purchase Order

Functional Group=PO

Purpose: This X12 Transaction Set contains the format and establishes the data contents of the Purchase Order Transaction Set (850) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide for customary and established business and industry practice relative to the placement of purchase orders for goods and services. This transaction set should not be used to convey purchase order changes or purchase order acknowledgment information.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	ST	Transaction Set Header	M	1			Must use
0200	BEG	Beginning Segment for Purchase Order	M	1			Must use
0500	REF	Reference Information	M	3			Must use
0600	PER	Administrative Communications Contact	O	3			Used
LOOP ID - SAC					25		
1200	SAC	Service, Promotion, Allowance, or Charge Information	O	1			Used
1300	ITD	Terms of Sale/Deferred Terms of Sale	O	1			Used
1500	DTM	Date/Time Reference	M	4			Must use
2300	TD1	Carrier Details (Quantity and Weight)	O	2			Used
2400	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1			Used
LOOP ID - N9					10		
2950	N9	Extended Reference Information	M	1			Must use
3000	MTX	Text	M	1			Must use
LOOP ID - N1					4		
3100	N1	Party Identification	M	1			Must use
3200	N2	Additional Name Information	O	2			Used
3300	N3	Party Location	O	2			Used
3400	N4	Geographic Location	O	1			Used
3600	PER	Administrative Communications Contact	O	1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - PO1					100000	N2/0100L	
0100	PO1	Baseline Item Data	M	1		N2/0100	Must use
LOOP ID - CTP					1		
0400	CTP	Pricing Information	O	1			Used
LOOP ID - PID					5		

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0500	PID	Product/Item Description	M	1			Must use
0900	PO4	Item Physical Details	O	>1			Used
1000	REF	Reference Information	M	>1			Must use
<u>LOOP ID - SAC</u>					<u>25</u>		
1300	SAC	Service, Promotion, Allowance, or Charge Information	O	1			Used
<u>LOOP ID - N9</u>					<u>10</u>		
3300	N9	Extended Reference Information	M	1			Must use
3400	MTX	Text	M	1			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
<u>LOOP ID - CTT</u>					<u>1</u>	<u>N3/0100L</u>	
0100	CTT	Transaction Totals	O	1		N3/0100	Used
0300	SE	Transaction Set Trailer	M	1			Must use

Notes:

- 2/0100L PO102 is required.
- 2/0100 PO102 is required.
- 3/0100L The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.
- 3/0100 The number of line items (CTT01) is the accumulation of the number of PO1 segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (PO102) for each PO1 segment.

General Usage:

Purchase Orders— Suppliers will be required to support the receipt of Purchase Order data from Shamrock Foods as part of the process of automating orders. Order types appear to suppliers as Bulk Shipments to the Distribution Center and Direct Shipments to the customer.

Change History:

06/07/2018

- Added additional SAC02 codes at both the header and the line item levels.

November 8, 2018

- The codes allowed in both the header and detail level SAC02 field have been updated. Please see segment for additional details.

*We have removed A170, A172, F050, F155, F330 and I390

*We have added F340, F800, G970, H040, H910

January 7, 2019

- Added new elements of PO105, PO402 and PO403. See segments for additional details.

February 13, 2019

- Added PO403 qualifiers of CN and PC, removed P1 as an option.

February 24, 2020

- Made Shamrock's SKU (PO106/PO107) mandatory

September 11, 2020

- Made Shamrock's SKU conditional. At least one of Shamrock SKU, vendor item number, UPC or GTIN will be sent

- Updated Department (REF02 when REF01=DP) to optional

- Added notes around PO Number stating it will be 8 characters long and numeric

- Updated PO105 to mandatory

January 22, 2021

- Updated the usernote for the PO number to indicate it will be between 8 and 10 characters long

ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

CodeList Summary (Total Codes: 318, Included: 1)

Code Name

850 Purchase Order

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
2. The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation convention to match the transaction set definition. When used, this implementation convention reference takes precedence over the implementation reference specified in the GS08.

BEG Beginning Segment for Purchase Order

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To indicate the beginning of the Purchase Order Transaction Set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BEG01	353	Transaction Set Purpose Code	M	ID	2/2	Must use

Description: Code identifying purpose of transaction set

CodeList Summary (Total Codes: 66, Included: 1)

Code Name

00 Original

BEG02	92	Purchase Order Type Code	M	ID	2/2	Must use
-------	----	--------------------------	---	----	-----	----------

Description: Code specifying the type of Purchase Order

CodeList Summary (Total Codes: 76, Included: 2)

Code Name

DR Direct Ship

SA Stand-alone Order

BEG03	324	Purchase Order Number	M	AN	1/22	Must use
-------	-----	-----------------------	---	----	------	----------

Description: Identifying number for Purchase Order assigned by the orderer/purchaser

User Note 1: Shamrock PO numbers will be between 8 and 10 characters long and numeric

BEG05	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

User Note 1: Purchase Order Date

Semantics:

1. BEG05 is the date assigned by the purchaser to purchase order.

REF Reference Information

Pos: 0500	Max: 3
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 3)

Code Name

CO Customer Order Number

DP Department Number

User Note 1:

Shamrock Foods Department ID - Optional

IA Internal Vendor Number

User Note 1:

Shamrock Foods assigned vendor ID - Required

REF02	127	Reference Identification	M	AN	1/50	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

PER Administrative Communications Contact

Pos: 0600	Max: 3
Heading - Optional	
Loop: N/A	Elements: 6

User Option (Usage): Used

Purpose: To identify a person or office to whom administrative communications should be directed

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code	M	ID	2/2	Must use
<p>Description: Code identifying the major duty or responsibility of the person or group named</p> <p>CodeList Summary (Total Codes: 238, Included: 1)</p> <p>Code Name</p> <p>BD Buyer Name or Department</p>						
PER02	93	Name	O	AN	1/60	Used
<p>Description: Free-form name</p>						
PER03	365	Communication Number Qualifier	X	ID	2/2	Used
<p>Description: Code identifying the type of communication number</p> <p>CodeList Summary (Total Codes: 42, Included: 1)</p> <p>Code Name</p> <p>TE Telephone</p>						
PER04	364	Communication Number	X	AN	1/256	Used
<p>Description: Complete communications number including country or area code when applicable</p>						
PER05	365	Communication Number Qualifier	X	ID	2/2	Used
<p>Description: Code identifying the type of communication number</p> <p>CodeList Summary (Total Codes: 42, Included: 1)</p> <p>Code Name</p> <p>EM Electronic Mail</p>						
PER06	364	Communication Number	X	AN	1/256	Used
<p>Description: Complete communications number including country or area code when applicable</p>						

Syntax Rules:

1. P0304 - If either PER03 or PER04 is present, then the other is required.
2. P0506 - If either PER05 or PER06 is present, then the other is required.
3. P0708 - If either PER07 or PER08 is present, then the other is required.

Loop Service, Promotion, Allowance, or Charge Information

Pos: 1200	Repeat: 25
Optional	
Loop: SAC	Elements: N/A

User Option (Usage): Used

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
1200	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Used

SAC Service, Promotion, Allowance, or Charge Information

Pos: 1200	Max: 1
Heading - Optional	
Loop: SAC	Elements: 4

User Option (Usage): Used

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC01	248	Allowance or Charge Indicator	M	ID	1/1	Must use

Description: Code which indicates an allowance or charge for the service specified

CodeList Summary (Total Codes: 7, Included: 2)

Code Name

A Allowance
C Charge

SAC02	1300	Service, Promotion, Allowance, or Charge Code	M	ID	4/4	Must use
-------	------	--	---	----	-----	----------

Description: Code identifying the service, promotion, allowance, or charge

CodeList Summary (Total Codes: 1090, Included: 7)

Code Name

D240 Freight
D270 Fuel Surcharge
F340 Pick/Up
F800 Promotional Allowance
G970 Small Order Charge
H040 Special Delivery
H910 Temperature Protection

SAC05	610	Amount	M	N2	1/15	Must use
-------	-----	---------------	---	----	------	----------

Description: Monetary amount

SAC15	352	Description	O	AN	1/80	Used
-------	-----	--------------------	---	----	------	------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. R0203 - At least one of SAC02 or SAC03 is required.
2. P0304 - If either SAC03 or SAC04 is present, then the other is required.
3. P0607 - If either SAC06 or SAC07 is present, then the other is required.
4. P0910 - If either SAC09 or SAC10 is present, then the other is required.
5. C1110 - If SAC11 is present, then SAC10 is required.
6. C1413 - If SAC14 is present, then SAC13 is required.
7. C1615 - If SAC16 is present, then SAC15 is required.

Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable to service, promotion, allowance, or charge.
7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.
8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the promotion.
9. SAC16 is used to identify the language being used in SAC15.

Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction with SAC03 to further define SAC02.
2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

ITD Terms of Sale/Deferred Terms of Sale

Pos: 1300	Max: 1
Heading - Optional	
Loop: N/A	Elements: 5

User Option (Usage): Used

Purpose: To specify terms of sale

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ITD02	333	Terms Basis Date Code	O	ID	1/2	Used

Description: Code identifying the beginning of the terms period

CodeList Summary (Total Codes: 17, Included: 3)

<u>Code</u>	<u>Name</u>
1	Ship Date
3	Invoice Date
15	Receipt of Goods

ITD03	338	Terms Discount Percent	O	R	1/6	Used
-------	-----	------------------------	---	---	-----	------

Description: Terms discount percentage, expressed as a percent, available to the purchaser if an invoice is paid on or before the Terms Discount Due Date

ITD05	351	Terms Discount Days Due	O	N0	1/3	Used
-------	-----	-------------------------	---	----	-----	------

Description: Number of days in the terms discount period by which payment is due if terms discount is earned

ITD07	386	Terms Net Days	O	N0	1/3	Used
-------	-----	----------------	---	----	-----	------

Description: Number of days until total invoice amount is due (discount not applicable)

ITD12	352	Description	O	AN	1/80	Used
-------	-----	-------------	---	----	------	------

Description: A free-form description to clarify the related data elements and their content

User Note 1: *Terms Description*

Syntax Rules:

1. L03040513 - If ITD03 is present, then at least one of ITD04, ITD05 or ITD13 is required.
2. L08040513 - If ITD08 is present, then at least one of ITD04, ITD05 or ITD13 is required.
3. L091011 - If ITD09 is present, then at least one of ITD10 or ITD11 is required.

Semantics:

1. ITD15 is the percentage applied to a base amount used to determine a late payment charge.

Comments:

1. If the code in ITD01 is "04", then ITD07 or ITD09 is required and either ITD10 or ITD11 is required; if the code in ITD01 is "05", then ITD06 or ITD07 is required.

DTM Date/Time Reference

Pos: 1500	Max: 4
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1280, Included: 2)

Code Name

002 Delivery Requested

User Note 1:

Used when the order is for vendor delivery

118 Requested Pickup

User Note 1:

Used when Shamrock will be picking the order up.

DTM02	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

User Note 1:

One of requested pick up or requested delivery dates (or both) will always be present.

TD1 Carrier Details (Quantity and Weight)

Pos: 2300	Max: 2
Heading - Optional	
Loop: N/A	Elements: 6

User Option (Usage): Used

Purpose: To specify the transportation details relative to commodity, weight, and quantity

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD101	103	Packaging Code	O	AN	3/5	Used
<p>Description: Code identifying the type of packaging; Part 1: Packaging Form, Part 2: Packaging Material; if the Data Element is used, then Part 1 is always required</p> <p>CodeList Summary (Total Codes: 155, Included: 1)</p> <p>Code Name</p> <p>CAS Case</p>						
TD102	80	Lading Quantity	O	N0	1/7	Used
<p>Description: Number of units (pieces) of the lading commodity</p>						
TD107	81	Weight	X	R	1/10	Used
<p>Description: Numeric value of weight</p>						
TD108	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
<p>Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken</p> <p>CodeList Summary (Total Codes: 844, Included: 2)</p> <p>Code Name</p> <p>KG Kilogram</p> <p>LB Pound</p>						
TD109	183	Volume	X	R	1/8	Used
<p>Description: Value of volumetric measure</p>						
TD110	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
<p>Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken</p> <p>CodeList Summary (Total Codes: 844, Included: 1)</p> <p>Code Name</p> <p>CF Cubic Feet</p>						

Syntax Rules:

1. C0102 - If TD101 is present, then TD102 is required.
2. C0304 - If TD103 is present, then TD104 is required.
3. C0607 - If TD106 is present, then TD107 is required.
4. P0708 - If either TD107 or TD108 is present, then the other is required.
5. P0910 - If either TD109 or TD110 is present, then the other is required.

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 2400	Max: 1
Heading - Optional	
Loop: N/A	Elements: 5

User Option (Usage): Used

Purpose: To specify the carrier and sequence of routing and provide transit time information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD502	66	Identification Code Qualifier	O	ID	1/2	Used

Description: Code designating the system/method of code structure used for Identification Code (67)

CodeList Summary (Total Codes: 241, Included: 1)

Code Name

2 Standard Carrier Alpha Code (SCAC)

TD503	67	Identification Code	O	AN	2/80	Used
-------	----	---------------------	---	----	------	------

Description: Code identifying a party or other code

User Note 1: SCAC

Min/ Max = 2/4

TD504	91	Transportation Method/Type Code	O	ID	1/2	Used
-------	----	---------------------------------	---	----	-----	------

Description: Code specifying the method or type of transportation for the shipment

CodeList Summary (Total Codes: 80, Included: 5)

Code Name

A Air

H Customer Pickup

User Note 1:

Used when Shamrock will be picking the order up.

M Motor (Common Carrier)

O Containerized Ocean

T Best Way (Shippers Option)

TD505	387	Routing	O	AN	1/35	Used
-------	-----	---------	---	----	------	------

Description: Free-form description of the routing or requested routing for shipment, or the originating carrier's identity

User Note 1: *Carrier Routing / Name*

TD512	284	Service Level Code	O	ID	2/2	Used
-------	-----	--------------------	---	----	-----	------

Description: Code indicating the level of transportation service or the billing service offered by the transportation carrier

CodeList Summary (Total Codes: 71, Included: 17)

Code Name

3D Three Day Service

CG Ground

CX Express Service

DC Delivery Confirmation

<u>Code</u>	<u>Name</u>
ET	Proof of Delivery (POD) with Signature
FC	First Class
G2	Standard Service
IE	Expedited Service - Worldwide
IX	Express Service - Worldwide
ND	Next Day Air
ON	Overnight
PB	Priority Mail
PI	Priority Mail Insured
SA	Same Day
SC	Second Day Air
SE	Second Day
SG	Standard Ground

Syntax Rules:

1. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.
2. C0203 - If TD502 is present, then TD503 is required.
3. C0708 - If TD507 is present, then TD508 is required.
4. C1011 - If TD510 is present, then TD511 is required.
5. C1312 - If TD513 is present, then TD512 is required.
6. C1413 - If TD514 is present, then TD513 is required.
7. C1512 - If TD515 is present, then TD512 is required.

Semantics:

1. TD515 is the country where the service is to be performed.

Comments:

1. When specifying a routing sequence to be used for the shipment movement in lieu of specifying each carrier within the movement, use TD502 to identify the party responsible for defining the routing sequence, and use TD503 to identify the actual routing sequence, specified by the party identified in TD502.

Loop Extended Reference Information

Pos: 2950	Repeat: 10
Optional	
Loop: N9	Elements: N/A

User Option (Usage): Used

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
2950	N9	Extended Reference Information	M	1		Must use
3000	MTX	Text	M	1		Must use

N9 Extended Reference Information

Pos: 2950	Max: 1
Heading - Mandatory	
Loop: N9	Elements: 2

User Option (Usage): Must use

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 1)

Code Name

L1 Letters or Notes

N902	127	Reference Identification	M	AN	1/50	Must use
------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

User Note 1:

N902 will contain one of the following 3 characters codes to identify the type of note to follow in MTX02.

- . GEN: General Note
- . SHP: Shipping Note
- . SPE: Special Instruction

Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

MTX Text

Pos: 3000	Max: 1
Heading - Mandatory	
Loop: N9	Elements: 1

User Option (Usage): Must use

Purpose: To specify textual data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MTX02	1551	Textual Data	M	AN	1/4096	Must use

Description: To transmit large volumes of message text

Syntax Rules:

1. C0102 - If MTX01 is present, then MTX02 is required.
2. C0302 - If MTX03 is present, then MTX02 is required.
3. C0504 - If MTX05 is present, then MTX04 is required.

Semantics:

1. MTX05 is the number of lines to advance before printing.

Comments:

1. If MTX04 is "AA - Advance the specific number of lines before print", then MTX05 is required.

Loop Party Identification

Pos: 3100	Repeat: 4
Mandatory	
Loop: N1	Elements: N/A

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
3100	N1	Party Identification	M	1		Must use
3200	N2	Additional Name Information	O	2		Used
3300	N3	Party Location	O	2		Used
3400	N4	Geographic Location	O	1		Used
3600	PER	Administrative Communications Contact	O	1		Used

User Note 1:

One iteration of the N1 loop will always be present for the Ship To (N101=ST) or Ship From (N101 = SF).

N1 Party Identification

Pos: 3100	Max: 1
Heading - Mandatory	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

CodeList Summary (Total Codes: 1500, Included: 4)

Code Name

BT Bill-to-Party
SF Ship From
ST Ship To
VN Vendor

N102	93	Name	O	AN	1/60	Used
------	----	-------------	---	----	------	------

Description: Free-form name

N103	66	Identification Code Qualifier	O	ID	1/2	Used
------	----	--------------------------------------	---	----	-----	------

Description: Code designating the system/method of code structure used for Identification Code (67)

CodeList Summary (Total Codes: 241, Included: 3)

Code Name

9 D-U-N-S+4, D-U-N-S Number with Four Character Suffix
92 Assigned by Buyer or Buyer's Agent
UL Global Location Number (GLN)

N104	67	Identification Code	O	AN	2/80	Used
------	----	----------------------------	---	----	------	------

Description: Code identifying a party or other code

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N2 Additional Name Information

Pos: 3200	Max: 2
Heading - Optional	
Loop: N1	Elements: 1

User Option (Usage): Used

Purpose: To specify additional names

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N201	93	Name	M	AN	1/60	Must use

Description: Free-form name

N3 Party Location

Pos: 3300	Max: 2
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

User Note 1:

Will be present when N101 = ST

N4 Geographic Location

Pos: 3400	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	O	AN	2/30	Used
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	O	ID	3/15	Used
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Used
		Description: Code identifying the country				

Syntax Rules:

1. E0207 - Only one of N402 or N407 may be present.
2. C0605 - If N406 is present, then N405 is required.
3. C0704 - If N407 is present, then N404 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

User Note 1:

Will be present when N101 = ST

PER Administrative Communications Contact

Pos: 3600	Max: 1
Heading - Optional	
Loop: N1	Elements: 8

User Option (Usage): Used

Purpose: To identify a person or office to whom administrative communications should be directed

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code	M	ID	2/2	Must use
		Description: Code identifying the major duty or responsibility of the person or group named				
		CodeList Summary (Total Codes: 238, Included: 1)				
		<u>Code</u> <u>Name</u>				
		IC Information Contact				
PER02	93	Name	O	AN	1/60	Used
		Description: Free-form name				
PER03	365	Communication Number Qualifier	X	ID	2/2	Used
		Description: Code identifying the type of communication number				
		CodeList Summary (Total Codes: 42, Included: 1)				
		<u>Code</u> <u>Name</u>				
		TE Telephone				
PER04	364	Communication Number	X	AN	1/256	Used
		Description: Complete communications number including country or area code when applicable				
PER05	365	Communication Number Qualifier	X	ID	2/2	Used
		Description: Code identifying the type of communication number				
		CodeList Summary (Total Codes: 42, Included: 1)				
		<u>Code</u> <u>Name</u>				
		EM Electronic Mail				
PER06	364	Communication Number	X	AN	1/256	Used
		Description: Complete communications number including country or area code when applicable				
PER07	365	Communication Number Qualifier	X	ID	2/2	Used
		Description: Code identifying the type of communication number				
		CodeList Summary (Total Codes: 42, Included: 1)				
		<u>Code</u> <u>Name</u>				
		FX Facsimile				
PER08	364	Communication Number	X	AN	1/256	Used
		Description: Complete communications number including country or area code when applicable				

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		applicable				

Syntax Rules:

1. P0304 - If either PER03 or PER04 is present, then the other is required.
2. P0506 - If either PER05 or PER06 is present, then the other is required.
3. P0708 - If either PER07 or PER08 is present, then the other is required.

Loop Baseline Item Data

Pos: 0100 Repeat: 100000
 Mandatory
 Loop: PO1 Elements: N/A

User Option (Usage): Must use

Purpose: To specify basic and most frequently used line item data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	PO1	Baseline Item Data	M	1		Must use
0400		Loop CTP	O		1	Used
0500		Loop PID	M		5	Must use
0900	PO4	Item Physical Details	O	>1		Used
1000	REF	Reference Information	M	>1		Must use
1300		Loop SAC	O		25	Used
3300		Loop N9	O		10	Used

PO1 Baseline Item Data

Pos: 0100 Max: 1
 Detail - Mandatory
 Loop: PO1 Elements: 13

User Option (Usage): Must use

Purpose: To specify basic and most frequently used line item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO101	350	Assigned Identification	O	AN	1/20	Used
Description: Alphanumeric characters assigned for differentiation within a transaction set						
User Note 1: PO Line #						
PO102	380	Quantity	M	R	1/15	Must use
Description: Numeric value of quantity						
PO103	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
CodeList Summary (Total Codes: 844, Included: 3)						
<u>Code</u> <u>Name</u>						
CA Case						
EA Each						
LB Pound						
PO104	212	Unit Price	M	R	1/17	Must use
Description: Price per unit of product, service, commodity, etc.						
User Note 1: Gross Purchase Price						
PO105	639	Basis of Unit Price Code	M	ID	2/2	Must use
Description: Code identifying the type of unit price for an item						
CodeList Summary (Total Codes: 91, Included: 2)						
<u>Code</u> <u>Name</u>						
PP Price per Pound						
UM Price per Unit of Measure						
PO106	235	Product/Service ID Qualifier	O	ID	2/2	Used
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
CodeList Summary (Total Codes: 519, Included: 1)						
<u>Code</u> <u>Name</u>						
SK Stock Keeping Unit (SKU)						
User Note 1:						
Shamrock Foods assigned SKU						
PO107	234	Product/Service ID	O	AN	1/48	Used
Description: Identifying number for a product or service						

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO108	235	Product/Service ID Qualifier	O	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 1)				
		Code Name				
		VN Vendor's (Seller's) Item Number				
PO109	234	Product/Service ID	O	AN	1/48	Used
		Description: Identifying number for a product or service				
PO110	235	Product/Service ID Qualifier	O	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 1)				
		Code Name				
		UK GTIN				
PO111	234	Product/Service ID	O	AN	1/48	Used
		Description: Identifying number for a product or service				
PO112	235	Product/Service ID Qualifier	O	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 1)				
		Code Name				
		UP UCC - 12				
PO113	234	Product/Service ID	O	AN	1/48	Used
		Description: Identifying number for a product or service				

Syntax Rules:

1. C0302 - If PO103 is present, then PO102 is required.
2. C0504 - If PO105 is present, then PO104 is required.
3. P0607 - If either PO106 or PO107 is present, then the other is required.
4. P0809 - If either PO108 or PO109 is present, then the other is required.
5. P1011 - If either PO110 or PO111 is present, then the other is required.
6. P1213 - If either PO112 or PO113 is present, then the other is required.
7. P1415 - If either PO114 or PO115 is present, then the other is required.
8. P1617 - If either PO116 or PO117 is present, then the other is required.
9. P1819 - If either PO118 or PO119 is present, then the other is required.
10. P2021 - If either PO120 or PO121 is present, then the other is required.
11. P2223 - If either PO122 or PO123 is present, then the other is required.
12. P2425 - If either PO124 or PO125 is present, then the other is required.

Semantics:

1. PO102 is quantity ordered.

Comments:

1. See the Data Element Dictionary for a complete list of IDs.
2. PO101 is the line item identification.
3. PO106 through PO125 provide for ten different product/service IDs per each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

User Note 1:

At least one of Shamrock's SKU, Vendor Part Number, UPC Number or GTIN Number will always be provided. The Shamrock Internal SKU will always be sent on the Purchase Order. It is optional but requested to be sent back on the return data.

Loop Pricing Information

Pos: 0400	Repeat: 1
Optional	
Loop: CTP	Elements: N/A

User Option (Usage): Used

Purpose: To specify pricing information

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0400	CTP	Pricing Information	O	1		Used

CTP Pricing Information

Pos: 0400	Max: 1
Detail - Optional	
Loop: CTP	Elements: 1

User Option (Usage): Used

Purpose: To specify pricing information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTP08	782	Monetary Amount	O	R	1/18	Used

Description: Monetary amount

User Note 1: *Extended Item Total (Price * Qty)*

Syntax Rules:

1. P0405 - If either CTP04 or CTP05 is present, then the other is required.
2. C0607 - If CTP06 is present, then CTP07 is required.
3. C0902 - If CTP09 is present, then CTP02 is required.
4. C1002 - If CTP10 is present, then CTP02 is required.
5. C1103 - If CTP11 is present, then CTP03 is required.

Semantics:

1. CTP07 is a multiplier factor to arrive at a final discounted price. A multiplier of .90 would be the factor if a 10% discount is given.
2. CTP08 is the rebate amount.

Comments:

1. See Figures Appendix for an example detailing the use of CTP03 and CTP04.
2. See Figures Appendix for an example detailing the use of CTP03, CTP04 and CTP07.

Loop Product/Item Description

Pos: 0500	Repeat: 5
Mandatory	
Loop: PID	Elements: N/A

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0500	PID	Product/Item Description	M	1		Must use

User Note 1:

The Product Description (PID05, when PID01=F and PID02=08) could repeat (up to 5 iterations) if needed.

PID Product/Item Description

Pos: 0500	Max: 1
Detail - Mandatory	
Loop: PID	Elements: 3

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use

Description: Code indicating the format of a description

CodeList Summary (Total Codes: 3, Included: 1)

Code Name

F Free-form

PID02	750	Product/Process Characteristic Code	M	ID	2/3	Must use
-------	-----	-------------------------------------	---	----	-----	----------

Description: Code identifying the general class of a product or process characteristic

CodeList Summary (Total Codes: 238, Included: 1)

Code Name

08 Product

PID05	352	Description	M	AN	1/80	Must use
-------	-----	-------------	---	----	------	----------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

PO4 Item Physical Details

Pos: 0900 Max: >1
 Detail - Optional
 Loop: PO1 Elements: 7

User Option (Usage): Used

Purpose: To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO401	356	Pack	O	N0	1/6	Used

Description: The number of inner containers, or number of eaches if there are no inner containers, per outer container

User Note 1: *Number of eaches in the master case.*

PO402	357	Size	X	R	1/8	Used
-------	-----	-------------	---	---	-----	------

Description: Size of supplier units in pack

PO403	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
-------	-----	---	---	----	-----	------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

CodeList Summary (Total Codes: 844, Included: 30)

<u>Code</u>	<u>Name</u>
5I	Standard Cubic Foot
91	Stokes
CA	Case
CC	Cubic Centimeter
CF	Cubic Feet
CM	Centimeter
CN	Can
DA	Days
DB	Dry Pounds
DR	Drum
DZ	Dozen
EA	Each
FO	Fluid Ounce
FT	Foot
GA	Gallon
GM	Grams per Sq. Meter
HR	Hours
IN	Inch
KG	Kilogram
LB	Pound
LT	Liter
MJ	Minutes
ML	Milliliter
OZ	Ounce - Av
PC	Piece
PK	Package

Code Name

PT Pint

QT Quart

RL Roll

UN Unit

PO406	384	Gross Weight per Pack	X	R	1/9	Used
-------	-----	------------------------------	---	---	-----	------

Description: Numeric value of gross weight per pack

PO407	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
-------	-----	---	---	----	-----	------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken**CodeList Summary** (Total Codes: 844, Included: 2)**Code Name**

KG Kilogram

LB Pound

PO408	385	Gross Volume per Pack	X	R	1/9	Used
-------	-----	------------------------------	---	---	-----	------

Description: Numeric value of gross volume per pack

PO409	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
-------	-----	---	---	----	-----	------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken**CodeList Summary** (Total Codes: 844, Included: 1)**Code Name**

CF Cubic Feet

Syntax Rules:

1. P0203 - If either PO402 or PO403 is present, then the other is required.
2. C0506 - If PO405 is present, then PO406 is required.
3. P0607 - If either PO406 or PO407 is present, then the other is required.
4. P0809 - If either PO408 or PO409 is present, then the other is required.
5. C1013 - If PO410 is present, then PO413 is required.
6. C1113 - If PO411 is present, then PO413 is required.
7. C1213 - If PO412 is present, then PO413 is required.
8. L13101112 - If PO413 is present, then at least one of PO410, PO411 or PO412 is required.
9. C1716 - If PO417 is present, then PO416 is required.
10. C1804 - If PO418 is present, then PO404 is required.

Semantics:

1. PO415 is used to indicate the relative layer of this package or range of packages within the layers of packaging. Relative Position 1 (value R1) is the innermost package.
2. PO416 is the package identifier or the beginning package identifier in a range of identifiers.
3. PO417 is the ending package identifier in a range of identifiers.
4. PO418 is the number of packages in this layer.

Comments:

1. PO403 - The "Unit or Basis for Measure Code" in this segment position is for purposes of defining the unit of measure of the "Size" identified in the PO402. For example: If the carton contains 24 12-Ounce packages, it

- would be described as follows: Data element 356 = "24"; Data element 357 = "12"; Data element 355 = "OZ".
2. PO413 defines the unit of measure for PO410, PO411, and PO412.

REF Reference Information

Pos: 1000	Max: >1
Detail - Mandatory	
Loop: PO1	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 1)

Code Name

2N Federal Communications Commission (FCC) Trade/Brand Identifier

User Note 1:

Brand

REF02	127	Reference Identification	M	AN	1/50	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop Service, Promotion, Allowance, or Charge Information

Pos: 1300 Repeat: 25
 Optional
 Loop: SAC Elements: N/A

User Option (Usage): Used

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
1300	SAC	Service, Promotion, Allowance, or Charge Information	O	1		Used

SAC Service, Promotion, Allowance, or Charge Information

Pos: 1300	Max: 1
Detail - Optional	
Loop: SAC	Elements: 4

User Option (Usage): Used

Purpose: To request or identify a service, promotion, allowance, or charge; to specify the amount or percentage for the service, promotion, allowance, or charge

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SAC01	248	Allowance or Charge Indicator	M	ID	1/1	Must use

Description: Code which indicates an allowance or charge for the service specified

CodeList Summary (Total Codes: 7, Included: 2)

Code Name

A Allowance
C Charge

SAC02	1300	Service, Promotion, Allowance, or Charge Code	M	ID	4/4	Must use
-------	------	---	---	----	-----	----------

Description: Code identifying the service, promotion, allowance, or charge

CodeList Summary (Total Codes: 1090, Included: 7)

Code Name

D240 Freight
D270 Fuel Surcharge
F340 Pick/Up
F800 Promotional Allowance
G970 Small Order Charge
H040 Special Delivery
H910 Temperature Protection

SAC05	610	Amount	M	N2	1/15	Must use
-------	-----	--------	---	----	------	----------

Description: Monetary amount

SAC15	352	Description	O	AN	1/80	Used
-------	-----	-------------	---	----	------	------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. R0203 - At least one of SAC02 or SAC03 is required.
2. P0304 - If either SAC03 or SAC04 is present, then the other is required.
3. P0607 - If either SAC06 or SAC07 is present, then the other is required.
4. P0910 - If either SAC09 or SAC10 is present, then the other is required.
5. C1110 - If SAC11 is present, then SAC10 is required.
6. C1413 - If SAC14 is present, then SAC13 is required.
7. C1615 - If SAC16 is present, then SAC15 is required.

Semantics:

1. If SAC01 is "A" or "C", then at least one of SAC05, SAC07, or SAC08 is required.
2. SAC05 is the total amount for the service, promotion, allowance, or charge.
3. If SAC05 is present with SAC07 or SAC08, then SAC05 takes precedence.
4. SAC08 is the allowance or charge rate per unit.
5. SAC10 and SAC11 is the quantity basis when the allowance or charge quantity is different from the purchase order or invoice quantity.
6. SAC10 and SAC11 used together indicate a quantity range, which could be a dollar amount, that is applicable to service, promotion, allowance, or charge.
7. SAC13 is used in conjunction with SAC02 or SAC04 to provide a specific reference number as identified by the code used.
8. SAC14 is used in conjunction with SAC13 to identify an option when there is more than one option of the promotion.
9. SAC16 is used to identify the language being used in SAC15.

Comments:

1. SAC04 may be used to uniquely identify the service, promotion, allowance, or charge. In addition, it may be used in conjunction with SAC03 to further define SAC02.
2. In some business applications, it is necessary to advise the trading partner of the actual dollar amount that a particular allowance, charge, or promotion was based on to reduce ambiguity. This amount is commonly referred to as "Dollar Basis Amount". It is represented in the SAC segment in SAC10 using the qualifier "DO" - Dollars in SAC09.

Loop Extended Reference Information

Pos: 3300	Repeat: 10
Optional	
Loop: N9	Elements: N/A

User Option (Usage): Used

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
3300	N9	Extended Reference Information	M	1		Must use
3400	MTX	Text	M	1		Must use

N9 Extended Reference Information

Pos: 3300	Max: 1
Detail - Mandatory	
Loop: N9	Elements: 2

User Option (Usage): Must use

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 1)

Code Name

L1 Letters or Notes

N902	127	Reference Identification	M	AN	1/50	Must use
------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

User Note 1:

N902 will contain one of the following 3 characters codes to identify the type of note to follow in MTX02.

- . GEN: General Note
- . SHP: Shipping Note
- . SPE: Special Instructions

Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

MTX Text

Pos: 3400	Max: 1
Detail - Mandatory	
Loop: N9	Elements: 1

User Option (Usage): Must use

Purpose: To specify textual data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MTX02	1551	Textual Data	M	AN	1/4096	Must use

Description: To transmit large volumes of message text

User Note 1:

If N902 =

- . *GEN - MTX02 is a General Note*
- . *SHP - MTX02 is a Shipping Note*
- . *SPE - MTX02 is a Special Instruction*

Syntax Rules:

1. C0102 - If MTX01 is present, then MTX02 is required.
2. C0302 - If MTX03 is present, then MTX02 is required.
3. C0504 - If MTX05 is present, then MTX04 is required.

Semantics:

1. MTX05 is the number of lines to advance before printing.

Comments:

1. If MTX04 is "AA - Advance the specific number of lines before print", then MTX05 is required.

Loop Transaction Totals

Pos: 0100	Repeat: 1
Optional	
Loop: CTT	Elements: N/A

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	CTT	Transaction Totals	O	1		Used

CTT Transaction Totals

Pos: 0100	Max: 1
Summary - Optional	
Loop: CTT	Elements: 1

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 0300	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.