

Daikin Applied Americas 856 Ship Notice/Manifest

X12/V4010/856: 856 Ship Notice/Manifest

Author:	SPS Commerce
Company:	Daikin Applied Americas
Publication:	11/1/2020
Modified:	11/17/2021

856 Ship Notice/Manifest

Functional Group=SH

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Ship Notice/Manifest Transaction Set (856) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to list the contents of a shipment of goods as well as additional information relating to the shipment, such as order information, product description, physical characteristics, type of packaging, marking, carrier information, and configuration of goods within the transportation equipment. The transaction set enables the sender to describe the contents and configuration of a shipment in various levels of detail and provides an ordered flexibility to convey information. The sender of this transaction is the organization responsible for detailing and communicating the contents of a shipment, or shipments, to one or more receivers of the transaction set. The receiver of this transaction set can be any organization having an interest in the contents of a shipment or information about the contents of a shipment.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BSN	Beginning Segment for Ship Notice	M	1			Must use
040	DTM	Date/Time Reference	M	2			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
110	TD1	Carrier Details (Quantity and Weight)	O	3			Used
120	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1			Used
150	REF	Reference Identification	M	7			Must use
210	FOB	F.O.B. Related Instructions	O	1			Used
LOOP ID - N1					2		
220	N1	Name	M	1			Must use
240	N3	Address Information	M	2			Must use
250	N4	Geographic Location	M	1			Must use
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
050	PRF	Purchase Order Reference	M	1			Must use
150	REF	Reference Identification	M	3			Must use
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
190	MAN	Marks and Numbers	M	1			Must use
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
020	LIN	Item Identification	M	1			Must use
030	SN1	Item Detail (Shipment)	M	1			Must use
070	PID	Product/Item Description	M	1			Must use
150	REF	Reference Identification	O	>1			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		N3/010	Used
020	SE	Transaction Set Trailer	M	1			Must use

Notes:

3/010 Number of line items (CTT01) is the accumulation of the number of HL segments. If used, hash total (CTT02) is the sum of the value of units shipped (SN102) for each SN1 segment.

Comments:

- 2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.

General Usage:

Advance Ship Notice – As confirmation of shipment and content information for visibility and automation of receiving, trading partners will be required to provide the ASN/Ship Notice details for all electronically created orders sent through SPS via EDI 856 or from one of SPS Commerce solutions (Web Fulfillment, System Automation).

Daikin Applied Americas will support the Pick and Pack and No Pack ASN Structure supporting both Carton, Pallet or Pallet and Carton packing and labeling and each ASN will represent a single shipment (Ship-To location). Trading Partners will be expected to include all PO's physically in a single Shipment/Trailer/Container within a single ASN data feed. If a Trading Partner is unable to consolidate orders within a single ASN feed, Daikin Applied Americas will support one ASN per order.

For Direct to Customer shipments, Trading Partners will be required to:

- *Include a single PO shipped to the end consumer within that single ASN data feed*
- *Provide a Packing slip within the consumer carton*

For DC shipments, Trading Partners can send the ASN data in -

- *SOTI (Shipment, Order, Tare/Pallet, Item - Primarily used for single SKU Pallets) format. With this format, Daikin Applied Americas would prefer the Trading Partner to provide the GS1 Shipping label at the Carton level and that the ASN data contains that barcode number.*
- *SOP1 (Shipment, Order, Pack/Carton, Item - used for loose Cartons and pallets containing more than one SKU) format. With this format, the Trading Partner is indicating they have provided the GS1 Shipping label at the Carton level and that the ASN data contains that barcode number.*

Change History:

*11/17/2021
Added the REF03 to the order level for the customer order number.*

10/28/2021

Updated the TD5 segment and TD502/03 to be optional.

08/23/2021

Added a note that the PO number must be 6/8 characters and numeric.

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

CodeList Summary (Total Codes: 298, Included: 1)

Code Name

856 Ship Notice/Manifest

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BSN Beginning Segment for Ship Notice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BSN01	353	Transaction Set Purpose Code	M	ID	2/2	Must use

Description: Code identifying purpose of transaction set

CodeList Summary (Total Codes: 65, Included: 1)

Code Name

00 Original

BSN02	396	Shipment Identification	M	AN	2/30	Must use
-------	-----	-------------------------	---	----	------	----------

Description: A unique control number assigned by the original shipper to identify a specific shipment

User Note 1: Unique Shipment ID Number

BSN03	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

User Note 1: ASN create date

BSN04	337	Time	M	TM	4/8	Must use
-------	-----	------	---	----	-----	----------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

User Note 1: ASN create time

Syntax Rules:

1. C0706 - If BSN07 is present, then BSN06 is required.

Semantics:

1. BSN03 is the date the shipment transaction set is created.
2. BSN04 is the time the shipment transaction set is created.
3. BSN06 is limited to shipment related codes.

DTM Date/Time Reference

Pos: 040	Max: 2
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1112, Included: 2)

Code Name

011 Shipped

User Note 1:

Mandatory

017 Estimated Delivery

User Note 1:

Mandatory

DTM02	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

Loop Hierarchical Level - Shipment

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
110	TD1	Carrier Details (Quantity and Weight)	O	3		Used
120	TD5	Carrier Details (Routing Sequence/Transit Time)	O	1		Used
150	REF	Reference Identification	M	7		Must use
210	FOB	F.O.B. Related Instructions	O	1		Used
220		Loop N1	M		2	Must use
010		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use

Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure

HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Code defining the characteristic of a level in a hierarchical structure

CodeList Summary (Total Codes: 170, Included: 1)

Code Name

S Shipment

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

TD1 Carrier Details (Quantity and Weight)

Pos: 110	Max: 3
Detail - Optional	
Loop: HL	Elements: 4

User Option (Usage): Used

Purpose: To specify the transportation details relative to commodity, weight, and quantity

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
TD102	80	Lading Quantity	O	N0	1/7	Used

Description: Number of units (pieces) of the lading commodity

TD106	187	Weight Qualifier	C	ID	1/2	Used
-------	-----	------------------	---	----	-----	------

Description: Code defining the type of weight

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

CodeList Summary (Total Codes: 51, Included: 3)

Code	Name
G	Gross Weight
N	Actual Net Weight
T	Tare Weight

User Note 1:
Weight of container

TD107	81	Weight	C	R	1/10	Used
-------	----	--------	---	---	------	------

Description: Numeric value of weight

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

TD108	355	Unit or Basis for Measurement Code	C	ID	2/2	Used
-------	-----	------------------------------------	---	----	-----	------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

CodeList Summary (Total Codes: 794, Included: 2)

Code	Name
KG	Kilogram
LB	Pound

Syntax Rules:

1. C0102 - If TD101 is present, then TD102 is required.
2. C0304 - If TD103 is present, then TD104 is required.
3. C0607 - If TD106 is present, then TD107 is required.
4. P0708 - If either TD107 or TD108 is present, then the other is required.
5. P0910 - If either TD109 or TD110 is present, then the other is required.

User Note 1:

TD1 segment can be repeated for each weight type (Gross, Net and Tare)

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 120	Max: 1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To specify the carrier and sequence of routing and provide transit time information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD502	66	Identification Code Qualifier	O	ID	1/2	Used

Description: Code designating the system/method of code structure used for Identification Code (67)

CodeList Summary (Total Codes: 215, Included: 1)

Code Name

2 Standard Carrier Alpha Code (SCAC)

TD503	67	Identification Code	O	AN	2/80	Used
-------	----	---------------------	---	----	------	------

Description: Code identifying a party or other code

User Note 1: *Min/max: 2/4*

Syntax Rules:

1. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.
2. C0203 - If TD502 is present, then TD503 is required.
3. C0708 - If TD507 is present, then TD508 is required.
4. C1011 - If TD510 is present, then TD511 is required.
5. C1312 - If TD513 is present, then TD512 is required.
6. C1413 - If TD514 is present, then TD513 is required.
7. C1512 - If TD515 is present, then TD512 is required.

Semantics:

1. TD515 is the country where the service is to be performed.

REF Reference Identification

Pos: 150	Max: 7
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

User Note 1: One of either Bill of Lading, Air Waybill, Carrier Pro Number or Tracking Number is required. A Tracking Number can be sent in place of a Carrier Pro number, but both should not be provided.

CodeList Summary (Total Codes: 1503, Included: 8)

Code Name

- 2I Tracking Number
- AW Air Waybill Number
- BM Bill of Lading Number
- CN Carrier's Reference Number (PRO/Invoice)
- L1 Letters or Notes
- OC Container Number
- PK Packing List Number
- TB Truck Number

REF02	127	Reference Identification	M	AN	1/30	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

FOB F.O.B. Related Instructions

Pos: 210	Max: 1
Detail - Optional	
Loop: HL	Elements: 1

User Option (Usage): Used

Purpose: To specify transportation instructions relating to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
FOB01	146	Shipment Method of Payment	M	ID	2/2	Must use

Description: Code identifying payment terms for transportation charges

CodeList Summary (Total Codes: 28, Included: 7)

<u>Code</u>	<u>Name</u>
BP	Paid by Buyer
CC	Collect
DF	Defined by Buyer and Seller
PP	Prepaid (by Seller)
PS	Paid by Seller
PU	Pickup
TP	Third Party Pay

Syntax Rules:

1. C0302 - If FOB03 is present, then FOB02 is required.
2. C0405 - If FOB04 is present, then FOB05 is required.
3. C0706 - If FOB07 is present, then FOB06 is required.
4. C0809 - If FOB08 is present, then FOB09 is required.

Semantics:

1. FOB01 indicates which party will pay the carrier.
2. FOB02 is the code specifying transportation responsibility location.
3. FOB06 is the code specifying the title passage location.
4. FOB08 is the code specifying the point at which the risk of loss transfers. This may be different than the location specified in FOB02/FOB03 and FOB06/FOB07.

Loop Name

Pos: 220	Repeat: 2
Mandatory	
Loop: N1	Elements: N/A

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
220	N1	Name	M	1		Must use
240	N3	Address Information	M	2		Must use
250	N4	Geographic Location	M	1		Must use

N1 Name

Pos: 220	Max: 1
Detail - Mandatory	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

CodeList Summary (Total Codes: 1312, Included: 2)

Code Name

SF Ship From

User Note 1:

Mandatory

ST Ship To

User Note 1:

Mandatory

N102	93	Name	M	AN	1/60	Must use
------	----	------	---	----	------	----------

Description: Free-form name

N103	66	Identification Code Qualifier	C	ID	1/2	Used
------	----	-------------------------------	---	----	-----	------

Description: Code designating the system/method of code structure used for Identification Code (67)

CodeList Summary (Total Codes: 215, Included: 1)

Code Name

92 Assigned by Buyer or Buyer's Agent

N104	67	Identification Code	C	AN	2/80	Used
------	----	---------------------	---	----	------	------

Description: Code identifying a party or other code

User Note 1: For N101 = ST, If provided on the order (850/860), required on the ASN

Required when N101 = SF, should be the value on the 850/860 provided in N104 when N101 = VN

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

N3 Address Information

Pos: 240	Max: 2
Detail - Mandatory	
Loop: N1	Elements: 2

User Option (Usage): Must use

Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 250	Max: 1
Detail - Mandatory	
Loop: N1	Elements: 6

User Option (Usage): Must use

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	M	AN	2/30	Must use
		Description: Free-form text for city name				
N402	156	State or Province Code	C	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
		User Note 1: N402 or N406 (N405 = CO) should be sent				
N403	116	Postal Code	M	ID	3/15	Must use
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	M	ID	2/3	Must use
		Description: Code identifying the country				
N405	309	Location Qualifier	C	ID	1/2	Must use
		Description: Code identifying type of location				
		CodeList Summary (Total Codes: 172, Included: 1)				
		Code Name				
		CO County/Parish and State				
N406	310	Location Identifier	C	AN	1/30	Used
		Description: Code which identifies a specific location				
		User Note 1: N402 or N406 (N405 = CO) should be sent				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Loop Hierarchical Level - Order

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
050	PRF	Purchase Order Reference	M	1		Must use
150	REF	Reference Identification	M	3		Must use
010		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 170, Included: 1)						
<u>Code</u> <u>Name</u>						
O Order						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

PRF Purchase Order Reference

Pos: 050	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To provide reference to a specific purchase order

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PRF01	324	Purchase Order Number	M	AN	1/22	Must use
Description: Identifying number for Purchase Order assigned by the orderer/purchaser						
User Note 1: <i>Purchase order numbers must be between 6/8 characters long and numeric</i>						
PRF02	328	Release Number	O	AN	1/30	Used
Description: Number identifying a release against a Purchase Order previously placed by the parties involved in the transaction						
User Note 1: <i>Return if present on the order (850/860)</i>						
PRF04	373	Date	O	DT	8/8	Used
Description: Date expressed as CCYYMMDD						
User Note 1: <i>PO Date</i>						

Semantics:

1. PRF04 is the date assigned by the purchaser to purchase order.

REF Reference Identification

Pos: 150	Max: 3
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1503, Included: 3)

Code Name

CO Customer Order Number

User Note 1:

Return if present on the order (850/860)

IA Internal Vendor Number

User Note 1:

Mandatory

Return value sent on the order (850/860)

PK Packing List Number

REF02	127	Reference Identification	C	AN	1/30	Used
-------	-----	--------------------------	---	----	------	------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

User Note 1: *Required when REF01=IA or PK*

REF03	352	Description	C	AN	1/80	Used
-------	-----	-------------	---	----	------	------

Description: A free-form description to clarify the related data elements and their content

User Note 1: *Required when REF01=CO*

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop Hierarchical Level - Pack

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
190	MAN	Marks and Numbers	M	1		Must use
010		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 170, Included: 2)						
<u>Code</u> <u>Name</u>						
P Pack						
T Shipping Tare						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

MAN Marks and Numbers

Pos: 190	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To indicate identifying marks and numbers for shipping containers

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
MAN01	88	Marks and Numbers Qualifier	M	ID	1/2	Must use

Description: Code specifying the application or source of Marks and Numbers (87)

User Note 1: *One of GM or CP must be provided*

CodeList Summary (Total Codes: 20, Included: 2)

Code Name

CP Carrier-Assigned Package ID Number

User Note 1:

Used with Parcel

GM SSCC-18 and Application Identifier

User Note 1:

Required for Direct to Warehouse/DC shipments

MAN02	87	Marks and Numbers	M	AN	1/48	Must use
-------	----	-------------------	---	----	------	----------

Description: Marks and numbers used to identify a shipment or parts of a shipment

Syntax Rules:

1. P0405 - If either MAN04 or MAN05 is present, then the other is required.
2. C0605 - If MAN06 is present, then MAN05 is required.

Semantics:

1. MAN01/MAN02 and MAN04/MAN05 may be used to identify two different marks and numbers assigned to the same physical container.
2. When both MAN02 and MAN03 are used, MAN02 is the starting number of a sequential range and MAN03 is the ending number of that range.
3. When both MAN05 and MAN06 are used, MAN05 is the starting number of a sequential range, and MAN06 is the ending number of that range.

Loop Hierarchical Level - Item

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
020	LIN	Item Identification	M	1		Must use
030	SN1	Item Detail (Shipment)	M	1		Must use
070	PID	Product/Item Description	M	1		Must use
150	REF	Reference Identification	O	>1		Used

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	O	AN	1/12	Used
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 170, Included: 1)						
<u>Code</u> <u>Name</u>						
I Item						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

LIN Item Identification

Pos: 020	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 7

User Option (Usage): Must use

Purpose: To specify basic item identification data

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
LIN01	350	Assigned Identification	M	AN	1/20	Must use

Description: Alphanumeric characters assigned for differentiation within a transaction set

User Note 1: Must match value sent on the Order (850/860)

LIN02	235	Product/Service ID Qualifier	X	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 1)

Code Name

BP Buyer's Part Number

User Note 1:

Return if present on the 850/860

LIN03	234	Product/Service ID	X	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

Description: Identifying number for a product or service

LIN04	235	Product/Service ID Qualifier	X	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 1)

Code Name

VP Vendor's (Seller's) Part Number

LIN05	234	Product/Service ID	X	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

Description: Identifying number for a product or service

LIN06	235	Product/Service ID Qualifier	X	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 1)

Code Name

CH Country of Origin Code

LIN07	234	Product/Service ID	X	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

Description: Identifying number for a product or service

User Note 1: 2 character ISO Code

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.
5. P1213 - If either LIN12 or LIN13 is present, then the other is required.
6. P1415 - If either LIN14 or LIN15 is present, then the other is required.
7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.
13. P2829 - If either LIN28 or LIN29 is present, then the other is required.
14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

Semantics:

1. LIN01 is the line item identification

SN1 Item Detail (Shipment)

Pos: 030	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify line-item detail relative to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SN102	382	Number of Units Shipped	M	R	1/10	Must use

Description: Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set

SN103	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
-------	-----	---	---	----	-----	----------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

CodeList Summary (Total Codes: 794, Included: 43)

<u>Code</u>	<u>Name</u>
05	5 Meter
12	12 PCS
18	55 Gallon Drum
30	30 Gallon Drum
5C	5 Gallon Drum
5I	Standard Cubic Foot
B8	Board Foot
CM	Centimeter
CS	Case
CY	Cubic Yard
DA	Days
DH	Miles
DO	Dollars, U.S.
DZ	Dozen
EA	Each
F2	Square Foot
FT	Foot
GL	Gallon
GS	Gross
HF	Hundred Feet
HH	Hundred Cubic Feet
HR	Hours
IN	Inch
KG	Kilogram
LB	Pound
LT	Liter
MM	Millimeter
MO	Months
MR	Meter
OP	Two pack

<u>Code</u>	<u>Name</u>
OZ	Ounce - Av
P4	Four-pack
P6	Six pack
P9	Nine pack
PR	Pair
PT	Pint
QT	Quart
RK	30FT Roll
SI	Square Inch
SM	Square Meter
TN	Net Ton
UN	Unit
YD	Yard

Syntax Rules:

1. P0506 - If either SN105 or SN106 is present, then the other is required.

Semantics:

1. SN101 is the ship notice line-item identification.

Comments:

1. SN103 defines the unit of measurement for both SN102 and SN104.

PID Product/Item Description

Pos: 070	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use

Description: Code indicating the format of a description

CodeList Summary (Total Codes: 3, Included: 1)

Code Name

F Free-form

PID02	750	Product/Process Characteristic Code	M	ID	2/3	Must use
-------	-----	-------------------------------------	---	----	-----	----------

Description: Code identifying the general class of a product or process characteristic

CodeList Summary (Total Codes: 217, Included: 1)

Code Name

08 Product

PID05	352	Description	M	AN	1/80	Must use
-------	-----	-------------	---	----	------	----------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

REF Reference Identification

Pos: 150	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1503, Included: 2)

Code Name

- L1 Letters or Notes
- SE Serial Number

REF02	127	Reference Identification	M	AN	1/30	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

- 1.

SE Transaction Set Trailer

Pos: 020	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.