

860 Purchase Order Change Request - Buyer Initiated

X12/V5010/860 : 860 Purchase Order Change Request - Buyer Initiated

Author:	SPS Commerce
Company:	Academy Sports and Outdoors

Table of Contents

860 Purchase Order Change Request - Buyer Initiated	1
ST Transaction Set Header	3
BCH Beginning Segment for Purchase Order Change	4
REF Reference Information	5
PER Administrative Communications Contact	6
FOB F.O.B. Related Instructions	7
ITD Terms of Sale/Deferred Terms of Sale	9
DTM Date/Time Reference	10
N9 Loop Extended Reference Information	11
N9 Extended Reference Information	12
MTX Text	13
N1 Loop Party Identification	14
N1 Party Identification	15
N3 Party Location	16
N4 Geographic Location	17
POC Loop Line Item Change	18
POC Line Item Change	19
CTP Pricing Information	22
PID Loop Product/Item Description	23
PID Product/Item Description	24
PO4 Item Physical Details	26
REF Reference Information	28
SDQ Destination Quantity	29
SLN Loop Subline Item Detail	32
SLN Subline Item Detail	33
PID Product/Item Description	35
CTT Loop Transaction Totals	36
CTT Transaction Totals	37
SE Transaction Set Trailer	38

860 Purchase Order Change Request - Buyer Initiated

Functional Group=**PC**

Purpose: This X12 Transaction Set contains the format and establishes the data contents of the Purchase Order Change Request - Buyer Initiated Transaction Set (860) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to provide the information required for the customary and established business and industry practice relative to a purchase order change. This transaction can be used: (1) by a buyer to request a change to a previously submitted purchase order or (2) by a buyer to confirm acceptance of a purchase order change initiated by the seller or by mutual agreement of the two parties.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
0100	ST	Transaction Set Header	M	1			Must use
0200	BCH	Beginning Segment for Purchase Order Change	M	1			Must use
0500	REF	Reference Information	M	4			Must use
0600	PER	Administrative Communications Contact	O	1			Used
0800	FOB	F.O.B. Related Instructions	M	1			Must use
1300	ITD	Terms of Sale/Deferred Terms of Sale	M	1			Must use
1500	DTM	Date/Time Reference	M	3			Must use
LOOP ID - N9					10		
2850	N9	Extended Reference Information	M	1			Must use
2900	MTX	Text	M	1			Must use
LOOP ID - N1					4		
3000	N1	Party Identification	M	1			Must use
3200	N3	Party Location	O	1			Used
3300	N4	Geographic Location	O	1			Used

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - POC					≥1		
0100	POC	Line Item Change	M	1			Must use
0400	CTP	Pricing Information	O	1			Used
LOOP ID - PID					10		
0500	PID	Product/Item Description	M	1			Must use
0900	PO4	Item Physical Details	M	1			Must use
1000	REF	Reference Information	O	1			Used
1900	SDQ	Destination Quantity	O	500			Used
LOOP ID - SLN					1000		
4600	SLN	Subline Item Detail	O	1			Used
4800	PID	Product/Item Description	O	1000			Used

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - CTT						1	N3/0100L
0100	CTT	Transaction Totals	O	1		N3/0100	Used
0300	SE	Transaction Set Trailer	M	1			Must use

Notes:

- 3/0100L Number of line items (CTT01) is the accumulation of the number of POC segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (POC03) for each POC segment.
- 3/0100 Number of line items (CTT01) is the accumulation of the number of POC segments. If used, hash total (CTT02) is the sum of the value of quantities ordered (POC03) for each POC segment.

User Note 1:

Change History

1/31/2019

- Updated N3 and N4 to Optional when N101 = FW (Freight Forwarder)
- Added N101 qualifier WH as Optional for Factory at the header level
- Removed line level N1 segment
- Updated header N101 qualifier 'CT' (Country of Origin) to Optional
- Added POC16/17(KL) as Optional for Hanging Status

2/4/2019

- Removed header DTM01 qualifier '002' (Delivery Requested) - Removed header TD1 segment
- Removed line PO405/06/07 (Weight)
- Removed line PO408/09 (Volume)

3/22/2019

- Updated N3 and N4 segments to Optional

9/5/2019

- Added DTM01 qualifiers 063 and 064

May 23, 2022

- Added detail level SLN loop to send component item details. See segments for additional information.

9/14/2022

- Added FOB05 qualifier of 'EXW'

10/10/2022

- Added header level REF01 qualifier of 'JD'
- Added subline item PID02 qualifiers of 92, 91 and 75.

ST Transaction Set Header

Pos: 0100	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

CodeList Summary (Total Codes: 318, Included: 1)

Code Name

860 Purchase Order Change Request - Buyer Initiated

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) is used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).
2. The implementation convention reference (ST03) is used by the translation routines of the interchange partners to select the appropriate implementation partners convention to match the transaction set definition. When used, this implementation convention reference takes precedence over the implementation reference specified in the GS08.

BCH Beginning Segment for Purchase Order Change

Pos: 0200	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 5

User Option (Usage): Must use

Purpose: To indicate the beginning of the Purchase Order Change Transaction Set and transmit identifying numbers and dates

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
BCH01	353	Transaction Set Purpose Code	M	ID	2/2	Must use

Description: Code identifying purpose of transaction set

CodeList Summary (Total Codes: 66, Included: 2)

Code Name

- 01 Cancellation
- 04 Change

BCH02	92	Purchase Order Type Code	M	ID	2/2	Must use
-------	----	--------------------------	---	----	-----	----------

Description: Code specifying the type of Purchase Order

CodeList Summary (Total Codes: 76, Included: 2)

Code Name

- KN Purchase Order

User Note 1:

Cross Dock

- SA Stand-alone Order

BCH03	324	Purchase Order Number	M	AN	1/22	Must use
-------	-----	-----------------------	---	----	------	----------

Description: Identifying number for Purchase Order assigned by the orderer/purchaser

BCH06	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

BCH11	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

Semantics:

1. BCH06 is the date assigned by the purchaser to purchase order.
2. BCH09 is the seller's order number.
3. BCH10 is the date assigned by the sender to the acknowledgment.
4. BCH11 is the date of the purchase order change request.

REF Reference Information

Pos: 0500	Max: 4
Heading - Mandatory	
Loop: N/A	Elements: 3

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 5)

Code Name

- 19 Division Identifier
- CB Combined Shipment
- DP Department Number
- IA Internal Vendor Number

User Note 1:

Mandatory

- JD User Identification

User Note 1:

Indicates how return data needs to be sent for prepack items

REF02	127	Reference Identification	M	AN	1/50	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

REF03	352	Description	X	AN	1/80	Used
-------	-----	-------------	---	----	------	------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

PER Administrative Communications Contact

Pos: 0600	Max: 1
Heading - Optional	
Loop: N/A	Elements: 2

User Option (Usage): Used

Purpose: To identify a person or office to whom administrative communications should be directed

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PER01	366	Contact Function Code	M	ID	2/2	Must use

Description: Code identifying the major duty or responsibility of the person or group named

CodeList Summary (Total Codes: 238, Included: 1)

Code Name

BD Buyer Name or Department

PER02	93	Name	M	AN	1/60	Must use
-------	----	------	---	----	------	----------

Description: Free-form name

Syntax Rules:

1. P0304 - If either PER03 or PER04 is present, then the other is required.
2. P0506 - If either PER05 or PER06 is present, then the other is required.
3. P0708 - If either PER07 or PER08 is present, then the other is required.

FOB F.O.B. Related Instructions

Pos: 0800	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 5

User Option (Usage): Must use

Purpose: To specify transportation instructions relating to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
FOB01	146	Shipment Method of Payment	M	ID	2/2	Must use

Description: Code identifying payment terms for transportation charges

CodeList Summary (Total Codes: 31, Included: 2)

Code Name

- CC Collect
- PP Prepaid (by Seller)

FOB02	309	Location Qualifier	M	ID	1/2	Must use
-------	-----	--------------------	---	----	-----	----------

Description: Code identifying type of location

CodeList Summary (Total Codes: 184, Included: 2)

Code Name

- DE Destination (Shipping)
- OR Origin (Shipping Point)

FOB03	352	Description	M	AN	1/80	Must use
-------	-----	-------------	---	----	------	----------

Description: A free-form description to clarify the related data elements and their content

FOB04	334	Transportation Terms Qualifier Code	O	ID	2/2	Used
-------	-----	-------------------------------------	---	----	-----	------

Description: Code identifying the source of the transportation terms

CodeList Summary (Total Codes: 3, Included: 1)

Code Name

- 01 Incoterms

FOB05	335	Transportation Terms Code	X	ID	3/3	Used
-------	-----	---------------------------	---	----	-----	------

Description: Code identifying the trade terms which apply to the shipment transportation responsibility

CodeList Summary (Total Codes: 24, Included: 5)

Code Name

- DAF Delivered at Frontier

User Note 1:

Delivered at Place

- DDP Delivered Duty Paid
- EXW Ex Works
- FCA Free Carrier
- FOB Free on Board

Syntax Rules:

1. C0302 - If FOB03 is present, then FOB02 is required.

2. C0405 - If FOB04 is present, then FOB05 is required.
3. C0706 - If FOB07 is present, then FOB06 is required.
4. C0809 - If FOB08 is present, then FOB09 is required.

Semantics:

1. FOB01 indicates which party will pay the carrier.
2. FOB02 is the code specifying transportation responsibility location.
3. FOB06 is the code specifying the title passage location.
4. FOB08 is the code specifying the point at which the risk of loss transfers. This may be different than the location specified in FOB02/FOB03 and FOB06/FOB07.

ITD Terms of Sale/Deferred Terms of Sale

Pos: 1300	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 1

User Option (Usage): Must use

Purpose: To specify terms of sale

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ITD12	352	Description	M	AN	1/80	Must use

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. L03040513 - If ITD03 is present, then at least one of ITD04, ITD05 or ITD13 is required.
2. L08040513 - If ITD08 is present, then at least one of ITD04, ITD05 or ITD13 is required.
3. L091011 - If ITD09 is present, then at least one of ITD10 or ITD11 is required.

Semantics:

1. ITD15 is the percentage applied to a base amount used to determine a late payment charge.

Comments:

1. If the code in ITD01 is "04", then ITD07 or ITD09 is required and either ITD10 or ITD11 is required; if the code in ITD01 is "05", then ITD06 or ITD07 is required.

DTM Date/Time Reference

Pos: 1500	Max: 3
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1280, Included: 4)

Code Name

- 037 Ship Not Before
- 038 Ship No Later
- 063 Do Not Deliver After
- 064 Do Not Deliver Before

DTM02	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD where CC represents the first two digits of the calendar year

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

User Note 1:

Either 037 and 038 (Ship Window) OR 063 and 064 (Delivery Window) will be sent on every order

Loop Extended Reference Information

Pos: 2850 Repeat: 10
 Optional
 Loop: N9 Elements: N/A

User Option (Usage): Used

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
2850	N9	Extended Reference Information	M	1		Must use
2900	MTX	Text	M	1		Must use

N9 Extended Reference Information

Pos: 2850	Max: 1
Heading - Mandatory	
Loop: N9	Elements: 2

User Option (Usage): Must use

Purpose: To transmit identifying information as specified by the Reference Identification Qualifier

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N901	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 1)

Code Name

L1 Letters or Notes

N902	127	Reference Identification	M	AN	1/50	Must use
------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

User Note 1: GEN: General Notes

Syntax Rules:

1. R0203 - At least one of N902 or N903 is required.
2. C0605 - If N906 is present, then N905 is required.

Semantics:

1. N906 reflects the time zone which the time reflects.
2. N907 contains data relating to the value cited in N902.

MTX Text

Pos: 2900	Max: 1
Heading - Mandatory	
Loop: N9	Elements: 1

User Option (Usage): Must use

Purpose: To specify textual data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MTX02	1551	Textual Data	X	AN	1/4096	Used

Description: To transmit large volumes of message text

Syntax Rules:

1. C0102 - If MTX01 is present, then MTX02 is required.
2. C0302 - If MTX03 is present, then MTX02 is required.
3. C0504 - If MTX05 is present, then MTX04 is required.

Semantics:

1. MTX05 is the number of lines to advance before printing.

Comments:

1. If MTX04 is "AA - Advance the specific number of lines before print", then MTX05 is required.

Loop Party Identification

Pos: 3000	Repeat: 4
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
3000	N1	Party Identification	M	1		Must use
3200	N3	Party Location	O	1		Used
3300	N4	Geographic Location	O	1		Used

N1 Party Identification

Pos: 3000	Max: 1
Heading - Mandatory	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

CodeList Summary (Total Codes: 1500, Included: 4)

Code Name

- CT Country of Origin
- FW Forwarder
- ST Ship To
- WH Warehouse

User Note 1:

Factory

N102	93	Name	X	AN	1/60	Used
------	----	------	---	----	------	------

Description: Free-form name

N103	66	Identification Code Qualifier	X	ID	1/2	Used
------	----	-------------------------------	---	----	-----	------

Description: Code designating the system/method of code structure used for Identification Code (67)

CodeList Summary (Total Codes: 241, Included: 1)

Code Name

- 92 Assigned by Buyer or Buyer's Agent

N104	67	Identification Code	X	AN	2/80	Used
------	----	---------------------	---	----	------	------

Description: Code identifying a party or other code

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N3 Party Location

Pos: 3200	Max: 1
Heading - Optional	
Loop: N1	Elements: 2

User Option (Usage): Used

Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 3300	Max: 1
Heading - Optional	
Loop: N1	Elements: 4

User Option (Usage): Used

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	C	AN	2/30	Used
Description: Free-form text for city name						
User Note 1: <i>Mandatory if N101 = FW or ST</i>						
N402	156	State or Province Code	C	ID	2/2	Used
Description: Code (Standard State/Province) as defined by appropriate government agency						
User Note 1: <i>Mandatory if N101 = FW or ST</i>						
N403	116	Postal Code	C	ID	3/15	Used
Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)						
User Note 1: <i>Mandatory if N101 = FW or ST</i>						
N404	26	Country Code	C	ID	2/3	Used
Description: Code identifying the country						
User Note 1: <i>Mandatory if N101 = FW or CT</i>						

Syntax Rules:

1. E0207 - Only one of N402 or N407 may be present.
2. C0605 - If N406 is present, then N405 is required.
3. C0704 - If N407 is present, then N404 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

Loop Line Item Change

Pos: 0100 Repeat: >1
 Optional
 Loop: POC Elements: N/A

User Option (Usage): Used

Purpose: To specify changes to a line item

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	POC	Line Item Change	M	1		Must use
0400	CTP	Pricing Information	O	1		Used
0500		Loop PID	M		10	Must use
0900	PO4	Item Physical Details	M	1		Must use
1000	REF	Reference Information	O	1		Used
1900	SDQ	Destination Quantity	O	500		Used
4600		Loop SLN	O		1000	Used

POC Line Item Change

Pos: 0100 Max: 1
 Detail - Mandatory
 Loop: POC Elements: 15

User Option (Usage): Must use

Purpose: To specify changes to a line item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
POC01	350	Assigned Identification	M	AN	1/20	Must use
		Description: Alphanumeric characters assigned for differentiation within a transaction set				
POC02	670	Change or Response Type Code	M	ID	2/2	Must use
		Description: Code specifying the type of change to the line item				
		CodeList Summary (Total Codes: 30, Included: 1)				
		<u>Code</u>	<u>Name</u>			
		RZ	Replace All Values			
POC03	380	Quantity	M	R	1/15	Must use
		Description: Numeric value of quantity				
POC05	C001	Composite Unit of Measure	M	Comp		Must use
		Description: To identify a composite unit of measure (See Figures Appendix for examples of use)				
POC05-01	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		CodeList Summary (Total Codes: 844, Included: 1)				
		<u>Code</u>	<u>Name</u>			
		EA	Each			
POC06	212	Unit Price	M	R	1/17	Must use
		Description: Price per unit of product, service, commodity, etc.				
POC08	235	Product/Service ID Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 1)				
		<u>Code</u>	<u>Name</u>			
		SK	Stock Keeping Unit (SKU)			
POC09	234	Product/Service ID	M	AN	1/48	Must use
		Description: Identifying number for a product or service				
POC10	235	Product/Service ID Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
		CodeList Summary (Total Codes: 519, Included: 1)				
		Code Name				
		VN Vendor's (Seller's) Item Number				
POC11	234	Product/Service ID	M	AN	1/48	Must use
		Description: Identifying number for a product or service				
POC12	235	Product/Service ID Qualifier	M	ID	2/2	Must use
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 1)				
		Code Name				
		UP UCC - 12				
POC13	234	Product/Service ID	M	AN	1/48	Must use
		Description: Identifying number for a product or service				
		User Note 1: Academy Sports uses a 14 digit value. Leading 0s maybe sent.				
POC14	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 1)				
		Code Name				
		ZZ Mutually Defined				
		User Note 1:				
		Ticket Type				
POC15	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				
POC16	235	Product/Service ID Qualifier	X	ID	2/2	Used
		Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)				
		CodeList Summary (Total Codes: 519, Included: 1)				
		Code Name				
		KL Item Management Code				
		User Note 1:				
		Hanging Status				
POC17	234	Product/Service ID	X	AN	1/48	Used
		Description: Identifying number for a product or service				

Syntax Rules:

1. P0305 - If either POC03 or POC05 is present, then the other is required.
2. C0405 - If POC04 is present, then POC05 is required.
3. C0706 - If POC07 is present, then POC06 is required.

4. P0809 - If either POC08 or POC09 is present, then the other is required.
5. P1011 - If either POC10 or POC11 is present, then the other is required.
6. P1213 - If either POC12 or POC13 is present, then the other is required.
7. P1415 - If either POC14 or POC15 is present, then the other is required.
8. P1617 - If either POC16 or POC17 is present, then the other is required.
9. P1819 - If either POC18 or POC19 is present, then the other is required.
10. P2021 - If either POC20 or POC21 is present, then the other is required.
11. P2223 - If either POC22 or POC23 is present, then the other is required.
12. P2425 - If either POC24 or POC25 is present, then the other is required.
13. P2627 - If either POC26 or POC27 is present, then the other is required.

Semantics:

1. POC01 is the purchase order line item identification.
2. POC03 is quantity ordered.

CTP Pricing Information

Pos: 0400	Max: 1
Detail - Optional	
Loop: POC	Elements: 2

User Option (Usage): Used

Purpose: To specify pricing information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTP02	236	Price Identifier Code	M	ID	3/3	Must use
Description: Code identifying pricing specification						
CodeList Summary (Total Codes: 168, Included: 1)						
<u>Code</u> <u>Name</u>						
RTL Retail						
CTP03	212	Unit Price	M	R	1/17	Must use
Description: Price per unit of product, service, commodity, etc.						

Syntax Rules:

1. P0405 - If either CTP04 or CTP05 is present, then the other is required.
2. C0607 - If CTP06 is present, then CTP07 is required.
3. C0902 - If CTP09 is present, then CTP02 is required.
4. C1002 - If CTP10 is present, then CTP02 is required.
5. C1103 - If CTP11 is present, then CTP03 is required.

Semantics:

1. CTP07 is a multiplier factor to arrive at a final discounted price. A multiplier of .90 would be the factor if a 10% discount is given.
2. CTP08 is the rebate amount.

Comments:

1. See Figures Appendix for an example detailing the use of CTP03 and CTP04.
2. See Figures Appendix for an example detailing the use of CTP03, CTP04 and CTP07.

Loop Product/Item Description

Pos: 0500	Repeat: 10
Mandatory	
Loop: PID	Elements: N/A

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0500	PID	Product/Item Description	M	1		Must use

PID Product/Item Description

Pos: 0500	Max: 1
Detail - Mandatory	
Loop: PID	Elements: 3

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
PID01	349	Item Description Type	M	ID	1/1	Must use

Description: Code indicating the format of a description

CodeList Summary (Total Codes: 3, Included: 1)

Code Name

F Free-form

PID02	750	Product/Process Characteristic Code	M	ID	2/3	Must use
-------	-----	-------------------------------------	---	----	-----	----------

Description: Code identifying the general class of a product or process characteristic

CodeList Summary (Total Codes: 238, Included: 4)

Code Name

08 Product

User Note 1:

Mandatory

75 Buyer's Color Description

91 Buyer's Item Size Description

92 Fabric Description

PID05	352	Description	M	AN	1/80	Must use
-------	-----	-------------	---	----	------	----------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.

3. PID07 specifies the individual code list of the agency specified in PID03.

PO4 Item Physical Details

Pos: 0900	Max: 1
Detail - Mandatory	
Loop: POC	Elements: 7

User Option (Usage): Must use

Purpose: To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO401	356	Pack	M	N0	1/6	Must use
Description: The number of inner containers, or number of eaches if there are no inner containers, per outer container						
PO402	357	Size	M	R	1/8	Must use
Description: Size of supplier units in pack						
PO403	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
CodeList Summary (Total Codes: 844, Included: 1)						
<u>Code</u> <u>Name</u>						
UN Unit						
PO410	82	Length	X	R	1/8	Used
Description: Largest horizontal dimension of an object measured when the object is in the upright position						
PO411	189	Width	X	R	1/8	Used
Description: Shorter measurement of the two horizontal dimensions measured with the object in the upright position						
PO412	65	Height	X	R	1/8	Used
Description: Vertical dimension of an object measured when the object is in the upright position						
PO413	355	Unit or Basis for Measurement Code	X	ID	2/2	Used
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
CodeList Summary (Total Codes: 844, Included: 1)						
<u>Code</u> <u>Name</u>						
IN Inch						

Syntax Rules:

1. P0203 - If either PO402 or PO403 is present, then the other is required.
2. C0506 - If PO405 is present, then PO406 is required.
3. P0607 - If either PO406 or PO407 is present, then the other is required.
4. P0809 - If either PO408 or PO409 is present, then the other is required.
5. C1013 - If PO410 is present, then PO413 is required.
6. C1113 - If PO411 is present, then PO413 is required.

7. C1213 - If PO412 is present, then PO413 is required.
8. L13101112 - If PO413 is present, then at least one of PO410, PO411 or PO412 is required.
9. C1716 - If PO417 is present, then PO416 is required.
10. C1804 - If PO418 is present, then PO404 is required.

Semantics:

1. PO415 is used to indicate the relative layer of this package or range of packages within the layers of packaging. Relative Position 1 (value R1) is the innermost package.
2. PO416 is the package identifier or the beginning package identifier in a range of identifiers.
3. PO417 is the ending package identifier in a range of identifiers.
4. PO418 is the number of packages in this layer.

Comments:

1. PO403 - The "Unit or Basis for Measure Code" in this segment position is for purposes of defining the unit of measure of the "Size" identified in the PO402. For example: If the carton contains 24 12-Ounce packages, it would be described as follows: Data element 356 = "24"; Data element 357 = "12"; Data element 355 = "OZ".
2. PO413 defines the unit of measure for PO410, PO411, and PO412.

REF Reference Information

Pos: 1000	Max: 1
Detail - Optional	
Loop: POC	Elements: 2

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1731, Included: 1)

Code Name

PG Product Group

User Note 1:

Product Subclass

REF02	127	Reference Identification	M	AN	1/50	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

SDQ Destination Quantity

Pos: 1900	Max: 500
Detail - Optional	
Loop: POC	Elements: 23

User Option (Usage): Used

Purpose: To specify destination and quantity detail

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SDQ01	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
		Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken				
		CodeList Summary (Total Codes: 844, Included: 1)				
		<u>Code</u>	<u>Name</u>			
		EA	Each			
SDQ02	66	Identification Code Qualifier	M	ID	1/2	Must use
		Description: Code designating the system/method of code structure used for Identification Code (67)				
		CodeList Summary (Total Codes: 241, Included: 1)				
		<u>Code</u>	<u>Name</u>			
		92	Assigned by Buyer or Buyer's Agent			
SDQ03	67	Identification Code	M	AN	2/80	Must use
		Description: Code identifying a party or other code				
SDQ04	380	Quantity	M	R	1/15	Must use
		Description: Numeric value of quantity				
SDQ05	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
SDQ06	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ07	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
SDQ08	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ09	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
SDQ10	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ11	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SDQ12	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ13	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
SDQ14	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ15	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
SDQ16	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ17	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
SDQ18	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ19	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
SDQ20	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ21	67	Identification Code	X	AN	2/80	Used
		Description: Code identifying a party or other code				
SDQ22	380	Quantity	X	R	1/15	Used
		Description: Numeric value of quantity				
SDQ23	310	Location Identifier	O	AN	1/30	Used
		Description: Code which identifies a specific location				

Syntax Rules:

1. P0506 - If either SDQ05 or SDQ06 is present, then the other is required.
2. P0708 - If either SDQ07 or SDQ08 is present, then the other is required.
3. P0910 - If either SDQ09 or SDQ10 is present, then the other is required.
4. P1112 - If either SDQ11 or SDQ12 is present, then the other is required.
5. P1314 - If either SDQ13 or SDQ14 is present, then the other is required.
6. P1516 - If either SDQ15 or SDQ16 is present, then the other is required.
7. P1718 - If either SDQ17 or SDQ18 is present, then the other is required.
8. P1920 - If either SDQ19 or SDQ20 is present, then the other is required.
9. P2122 - If either SDQ21 or SDQ22 is present, then the other is required.

Semantics:

1. SDQ23 identifies the area within the location identified in SDQ03, SDQ05, SDQ07, SDQ09, SDQ11, SDQ13, SDQ15, SDQ17, SDQ19, and SDQ21.

Comments:

1. SDQ02 is used only if different than previously defined in the transaction set.
2. SDQ03 is the store number.
3. SDQ23 may be used to identify areas within a store, e.g., front room, back room, selling outpost, end aisle display, etc. The value is agreed to by trading partners or industry conventions.

Loop Subline Item Detail

Pos: 4600	Repeat: 1000
Optional	
Loop: SLN	Elements: N/A

User Option (Usage): Used

Purpose: To specify product subline detail item data

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
4600	SLN	Subline Item Detail	O	1		Used
4800	PID	Product/Item Description	O	1000		Used

SLN Subline Item Detail

Pos: 4600 Max: 1
 Detail - Optional
 Loop: SLN Elements: 10

User Option (Usage): Used

Purpose: To specify product subline detail item data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SLN01	350	Assigned Identification	M	AN	1/20	Must use
Description: Alphanumeric characters assigned for differentiation within a transaction set						
SLN03	662	Relationship Code	M	ID	1/1	Must use
Description: Code indicating the relationship between entities						
CodeList Summary (Total Codes: 5, Included: 1)						
<u>Code</u> <u>Name</u>						
I Included						
SLN04	380	Quantity	X	R	1/15	Used
Description: Numeric value of quantity						
User Note 1: Amount of the component item in the prepack. PO102 * SLN04 = total amount of this SKU being ordered.						
SLN05	C001	Composite Unit of Measure	X	Comp		Used
Description: To identify a composite unit of measure (See Figures Appendix for examples of use)						
SLN05-01	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken						
CodeList Summary (Total Codes: 844, Included: 1)						
<u>Code</u> <u>Name</u>						
EA Each						
SLN09	235	Product/Service ID Qualifier	M	ID	2/2	Must use
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
CodeList Summary (Total Codes: 519, Included: 1)						
<u>Code</u> <u>Name</u>						
UP UCC - 12						
SLN10	234	Product/Service ID	M	AN	1/48	Must use
Description: Identifying number for a product or service						
SLN11	235	Product/Service ID Qualifier	X	ID	2/2	Used
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)						
CodeList Summary (Total Codes: 519, Included: 1)						

		<u>Code</u>	<u>Name</u>				
		SK	Stock Keeping Unit (SKU)				
SLN12	234	Product/Service ID		X	AN	1/48	Used
Description: Identifying number for a product or service							
SLN13	235	Product/Service ID Qualifier		X	ID	2/2	Used
Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)							
CodeList Summary (Total Codes: 519, Included: 1)							
		<u>Code</u>	<u>Name</u>				
		VN	Vendor's (Seller's) Item Number				
SLN14	234	Product/Service ID		X	AN	1/48	Used
Description: Identifying number for a product or service							

Syntax Rules:

1. P0405 - If either SLN04 or SLN05 is present, then the other is required.
2. C0706 - If SLN07 is present, then SLN06 is required.
3. C0806 - If SLN08 is present, then SLN06 is required.
4. P0910 - If either SLN09 or SLN10 is present, then the other is required.
5. P1112 - If either SLN11 or SLN12 is present, then the other is required.
6. P1314 - If either SLN13 or SLN14 is present, then the other is required.
7. P1516 - If either SLN15 or SLN16 is present, then the other is required.
8. P1718 - If either SLN17 or SLN18 is present, then the other is required.
9. P1920 - If either SLN19 or SLN20 is present, then the other is required.
10. P2122 - If either SLN21 or SLN22 is present, then the other is required.
11. P2324 - If either SLN23 or SLN24 is present, then the other is required.
12. P2526 - If either SLN25 or SLN26 is present, then the other is required.
13. P2728 - If either SLN27 or SLN28 is present, then the other is required.

Semantics:

1. SLN01 is the identifying number for the subline item.
2. SLN02 is the identifying number for the subline level. The subline level is analogous to the level code used in a bill of materials.
3. SLN03 is the configuration code indicating the relationship of the subline item to the baseline item.
4. SLN08 is a code indicating the relationship of the price or amount to the associated segment.

Comments:

1. See the Data Element Dictionary for a complete list of IDs.
2. SLN01 is related to (but not necessarily equivalent to) the baseline item number. Example: 1.1 or 1A might be used as a subline number to relate to baseline number 1.
3. SLN09 through SLN28 provide for ten different product/service IDs for each item. For example: Case, Color, Drawing No., U.P.C. No., ISBN No., Model No., or SKU.

PID Product/Item Description

Pos: 4800	Max: 1000
Detail - Optional	
Loop: SLN	Elements: 3

User Option (Usage): Used

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use

Description: Code indicating the format of a description

CodeList Summary (Total Codes: 3, Included: 1)

Code Name

F Free-form

PID02	750	Product/Process Characteristic Code	M	ID	2/3	Must use
-------	-----	-------------------------------------	---	----	-----	----------

Description: Code identifying the general class of a product or process characteristic

CodeList Summary (Total Codes: 238, Included: 4)

Code Name

08 Product
 75 Buyer's Color Description
 91 Buyer's Item Size Description
 92 Fabric Description

PID05	352	Description	M	AN	1/80	Must use
-------	-----	-------------	---	----	------	----------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

Comments:

1. If PID01 equals "F", then PID05 is used. If PID01 equals "S", then PID04 is used. If PID01 equals "X", then both PID04 and PID05 are used.
2. Use PID06 when necessary to refer to the product surface or layer being described in the segment.
3. PID07 specifies the individual code list of the agency specified in PID03.

Loop Transaction Totals

Pos: 0100	Repeat: 1
Optional	
Loop: CTT	Elements: N/A

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
0100	CTT	Transaction Totals	O	1		Used

CTT Transaction Totals

Pos: 0100	Max: 1
Summary - Optional	
Loop: CTT	Elements: 1

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

1. This segment is intended to provide hash totals to validate transaction completeness and correctness.

SE Transaction Set Trailer

Pos: 0300	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.