

Vallen Distribution, Inc. 856 Ship Notice/Manifest

X12/V4010/856: 856 Ship Notice/Manifest

Author:	SPS Commerce
Company:	Vallen Distribution, Inc.
Publication:	10/5/2020
Modified:	5/18/2021

856 Ship Notice/Manifest

Functional Group=SH

Purpose: This Draft Standard for Trial Use contains the format and establishes the data contents of the Ship Notice/Manifest Transaction Set (856) for use within the context of an Electronic Data Interchange (EDI) environment. The transaction set can be used to list the contents of a shipment of goods as well as additional information relating to the shipment, such as order information, product description, physical characteristics, type of packaging, marking, carrier information, and configuration of goods within the transportation equipment. The transaction set enables the sender to describe the contents and configuration of a shipment in various levels of detail and provides an ordered flexibility to convey information. The sender of this transaction is the organization responsible for detailing and communicating the contents of a shipment, or shipments, to one or more receivers of the transaction set. The receiver of this transaction set can be any organization having an interest in the contents of a shipment or information about the contents of a shipment.

Heading:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	ST	Transaction Set Header	M	1			Must use
020	BSN	Beginning Segment for Ship Notice	M	1			Must use
040	DTM	Date/Time Reference	M	2			Must use

Detail:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
110	TD1	Carrier Details (Quantity and Weight)	O	2			Used
120	TD5	Carrier Details (Routing Sequence/Transit Time)	M	1			Must use
150	REF	Reference Identification	M	2			Must use
LOOP ID - N1					2		
220	N1	Name	M	1			Must use
240	N3	Address Information	M	2			Must use
250	N4	Geographic Location	M	1			Must use
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
050	PRF	Purchase Order Reference	M	1			Must use
150	REF	Reference Identification	M	3			Must use
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
060	PO4	Item Physical Details	O	1			Used
190	MAN	Marks and Numbers	M	1			Must use
LOOP ID - HL					200000	C2/010L	
010	HL	Hierarchical Level	M	1		C2/010	Must use
020	LIN	Item Identification	M	1			Must use
030	SN1	Item Detail (Shipment)	M	1			Must use
060	PO4	Item Physical Details	O	1			Used
070	PID	Product/Item Description	M	1			Must use

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
150	REF	Reference Identification	O	>1			Used
200	DTM	Date/Time Reference	O	2			Used
LOOP ID - N1					1		
220	N1	Name	M	1			Must use
250	N4	Geographic Location	M	1			Must use

Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Notes</u>	<u>Usage</u>
010	CTT	Transaction Totals	O	1		N3/010	Used
020	SE	Transaction Set Trailer	M	1			Must use

Notes:

3/010 Number of line items (CTT01) is the accumulation of the number of HL segments. If used, hash total (CTT02) is the sum of the value of units shipped (SN102) for each SN1 segment.

Comments:

- 2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010L The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.
- 2/010 The HL segment is the only mandatory segment within the HL loop, and by itself, the HL segment has no meaning.

General Usage:

Advance Ship Notice – As confirmation of shipment and content information for visibility and automation of receiving, trading partners will be required to provide the ASN/Ship Notice details for all electronically created orders sent through SPS via EDI 856 or from one of SPS Commerce solutions (Web Fulfillment, System Automation).

Vallen will support the Pick and Pack ASN Structure supporting both Carton, Pallet or Pallet and Carton packing and labeling and each ASN will represent a single shipment (Ship-To location). Trading Partners will be expected to include all PO's physically in a single Shipment/Trailer/Container within a single ASN data feed. If a Trading Partner is unable to consolidate orders within a single ASN feed, Vallen will support one ASN per order.

For Direct to Customer shipments, Trading Partners will be required to:

- Include a single PO shipped to the end consumer within that single ASN data feed*
- Provide a Packing slip within the consumer carton. It is preferred that the Packing Slip be Branded with Vallen's logo however the branding/logo is not a requirement*

For DC shipments, Trading Partners can send the ASN data in -

- SOTI (Shipment, Order, Tare/Pallet, Item - Primarily used for single SKU Pallets) format. With this format, Vallen would prefer the Trading Partner to provide the GS1 Shipping label at the Carton level and that the ASN data*

contains that barcode number.

- *SOP1 (Shipment, Order, Pack/Carton, Item - used for loose Cartons and pallets containing more than one SKU) format. With this format, the Trading Partner is indicating they have provided the GS1 Shipping label at the Carton level and that the ASN data contains that barcode number.*

Change History:

05/18/2021 - Changed LIN03 from mandatory to conditionally required when sent on the PO (EDI 850)

ST Transaction Set Header

Pos: 010	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the start of a transaction set and to assign a control number

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
ST01	143	Transaction Set Identifier Code	M	ID	3/3	Must use

Description: Code uniquely identifying a Transaction Set

CodeList Summary (Total Codes: 298, Included: 1)

Code Name

856 Ship Notice/Manifest

ST02	329	Transaction Set Control Number	M	AN	4/9	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set

Semantics:

1. The transaction set identifier (ST01) used by the translation routines of the interchange partners to select the appropriate transaction set definition (e.g., 810 selects the Invoice Transaction Set).

BSN Beginning Segment for Ship Notice

Pos: 020	Max: 1
Heading - Mandatory	
Loop: N/A	Elements: 4

User Option (Usage): Must use

Purpose: To transmit identifying numbers, dates, and other basic data relating to the transaction set

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
BSN01	353	Transaction Set Purpose Code	M	ID	2/2	Must use

Description: Code identifying purpose of transaction set

CodeList Summary (Total Codes: 65, Included: 2)

Code Name

00	Original
06	Confirmation

User Note 1:

Please return '06' when the PO BEG02 = DS/POC BCH02 = DS

BSN02	396	Shipment Identification	M	AN	2/30	Must use
-------	-----	-------------------------	---	----	------	----------

Description: A unique control number assigned by the original shipper to identify a specific shipment

User Note 1: *Unique Shipment ID Number*

BSN03	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

User Note 1: *ASN create date*

BSN04	337	Time	M	TM	4/8	Must use
-------	-----	------	---	----	-----	----------

Description: Time expressed in 24-hour clock time as follows: HHMM, or HHMMSS, or HHMMSSD, or HHMMSSDD, where H = hours (00-23), M = minutes (00-59), S = integer seconds (00-59) and DD = decimal seconds; decimal seconds are expressed as follows: D = tenths (0-9) and DD = hundredths (00-99)

User Note 1: *ASN create time*

Syntax Rules:

1. C0706 - If BSN07 is present, then BSN06 is required.

Semantics:

1. BSN03 is the date the shipment transaction set is created.
2. BSN04 is the time the shipment transaction set is created.
3. BSN06 is limited to shipment related codes.

Comments:

- 1.

DTM Date/Time Reference

Pos: 040	Max: 2
Heading - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1112, Included: 2)

Code Name

011 Shipped

User Note 1:

Mandatory

017 Estimated Delivery

User Note 1:

Mandatory

DTM02	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

Loop Hierarchical Level - Shipment

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
110	TD1	Carrier Details (Quantity and Weight)	O	2		Used
120	TD5	Carrier Details (Routing Sequence/Transit Time)	M	1		Must use
150	REF	Reference Identification	M	2		Must use
220		Loop N1	M		2	Must use
010		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use

Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure

HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
------	-----	--------------------------------	---	----	-----	----------

Description: Code defining the characteristic of a level in a hierarchical structure

CodeList Summary (Total Codes: 170, Included: 1)

Code Name

S Shipment

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

TD1 Carrier Details (Quantity and Weight)

Pos: 110	Max: 2
Detail - Optional	
Loop: HL	Elements: 5

User Option (Usage): Used

Purpose: To specify the transportation details relative to commodity, weight, and quantity

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD101	103	Packaging Code	M	AN	3/5	Must use

Description: Code identifying the type of packaging; Part 1: Packaging Form, Part 2: Packaging Material; if the Data Element is used, then Part 1 is always required

CodeList Summary (Total Codes: 148, Included: 2)

<u>Code</u>	<u>Name</u>
CTN	Carton
PLT	Pallet

TD102	80	Lading Quantity	M	N0	1/7	Must use
-------	----	-----------------	---	----	-----	----------

Description: Number of units (pieces) of the lading commodity

TD106	187	Weight Qualifier	C	ID	1/2	Used
-------	-----	------------------	---	----	-----	------

Description: Code defining the type of weight

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

CodeList Summary (Total Codes: 51, Included: 1)

<u>Code</u>	<u>Name</u>
G	Gross Weight

TD107	81	Weight	C	R	1/10	Used
-------	----	--------	---	---	------	------

Description: Numeric value of weight

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

TD108	355	Unit or Basis for Measurement Code	C	ID	2/2	Used
-------	-----	------------------------------------	---	----	-----	------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

CodeList Summary (Total Codes: 794, Included: 1)

<u>Code</u>	<u>Name</u>
LB	Pound

Syntax Rules:

1. C0102 - If TD101 is present, then TD102 is required.
2. C0304 - If TD103 is present, then TD104 is required.
3. C0607 - If TD106 is present, then TD107 is required.
4. P0708 - If either TD107 or TD108 is present, then the other is required.
5. P0910 - If either TD109 or TD110 is present, then the other is required.

TD5 Carrier Details (Routing Sequence/Transit Time)

Pos: 120	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 5

User Option (Usage): Must use

Purpose: To specify the carrier and sequence of routing and provide transit time information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
TD502	66	Identification Code Qualifier	M	ID	1/2	Used
<p>Description: Code designating the system/method of code structure used for Identification Code (67)</p> <p>CodeList Summary (Total Codes: 215, Included: 1)</p> <p>Code Name</p> <p>2 Standard Carrier Alpha Code (SCAC)</p>						
TD503	67	Identification Code	M	AN	2/80	Used
<p>Description: Code identifying a party or other code</p>						
TD504	91	Transportation Method/Type Code	O	ID	1/2	Used
<p>Description: Code specifying the method or type of transportation for the shipment</p> <p>CodeList Summary (Total Codes: 71, Included: 6)</p> <p>Code Name</p> <p>A Air</p> <p>M Motor (Common Carrier)</p> <p>O Containerized Ocean</p> <p>P Private Carrier</p> <p>R Rail</p> <p>LT Less Than Trailer Load (LTL)</p>						
TD505	387	Routing	M	AN	1/35	Must use
<p>Description: Free-form description of the routing or requested routing for shipment, or the originating carrier's identity</p>						
TD512	284	Service Level Code	O	ID	2/2	Used
<p>Description: Code indicating the level of transportation service or the billing service offered by the transportation carrier</p> <p>CodeList Summary (Total Codes: 66, Included: 12)</p> <p>Code Name</p> <p>3D Three Day Service</p> <p>AM A.M.</p> <p>CG Ground</p> <p>CX Express Service</p> <p>FC First Class</p> <p>ND Next Day Air</p> <p>ON Overnight</p> <p>PB Priority Mail</p>						

<u>Code</u>	<u>Name</u>
SA	Same Day
SC	Second Day Air
SD	Saturday
SE	Second Day

Syntax Rules:

1. R0204050612 - At least one of TD502, TD504, TD505, TD506 or TD512 is required.
2. C0203 - If TD502 is present, then TD503 is required.
3. C0708 - If TD507 is present, then TD508 is required.
4. C1011 - If TD510 is present, then TD511 is required.
5. C1312 - If TD513 is present, then TD512 is required.
6. C1413 - If TD514 is present, then TD513 is required.
7. C1512 - If TD515 is present, then TD512 is required.

Semantics:

1. TD515 is the country where the service is to be performed.

Comments:

- 1.

REF Reference Identification

Pos: 150	Max: 2
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

User Note 1: One of either Bill of Lading, Carrier Pro Number or Tracking Number is required. A Tracking Number can be sent in place of a Carrier Pro number, but both should not be provided.

CodeList Summary (Total Codes: 1503, Included: 3)

Code Name

2I	Tracking Number
BM	Bill of Lading Number
CN	Carrier's Reference Number (PRO/Invoice)

REF02	127	Reference Identification	M	AN	1/30	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop Name

Pos: 220	Repeat: 2
Mandatory	
Loop: N1	Elements: N/A

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
220	N1	Name	M	1		Must use
240	N3	Address Information	M	2		Must use
250	N4	Geographic Location	M	1		Must use

N1 Name

Pos: 220	Max: 1
Detail - Mandatory	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

Ref	Id	Element Name	Req	Type	Min/Max	Usage
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

CodeList Summary (Total Codes: 1312, Included: 2)

Code Name

SF Ship From

User Note 1:

Mandatory

ST Ship To

User Note 1:

Mandatory

N102	93	Name	M	AN	1/60	Must use
------	----	------	---	----	------	----------

Description: Free-form name

N103	66	Identification Code Qualifier	X	ID	1/2	Used
------	----	-------------------------------	---	----	-----	------

Description: Code designating the system/method of code structure used for Identification Code (67)

CodeList Summary (Total Codes: 215, Included: 1)

Code Name

92 Assigned by Buyer or Buyer's Agent

N104	67	Identification Code	X	AN	2/80	Used
------	----	---------------------	---	----	------	------

Description: Code identifying a party or other code

User Note 1: *If provided on the order (850/860), required on the ASN*

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

- 1.

N3 Address Information

Pos: 240	Max: 2
Detail - Mandatory	
Loop: N1	Elements: 2

User Option (Usage): Must use

Purpose: To specify the location of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N301	166	Address Information	M	AN	1/55	Must use
		Description: Address information				
N302	166	Address Information	O	AN	1/55	Used
		Description: Address information				

N4 Geographic Location

Pos: 250	Max: 1
Detail - Mandatory	
Loop: N1	Elements: 4

User Option (Usage): Must use

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N401	19	City Name	M	AN	2/30	Must use
		Description: Free-form text for city name				
N402	156	State or Province Code	O	ID	2/2	Used
		Description: Code (Standard State/Province) as defined by appropriate government agency				
N403	116	Postal Code	M	ID	3/15	Must use
		Description: Code defining international postal zone code excluding punctuation and blanks (zip code for United States)				
N404	26	Country Code	O	ID	2/3	Used
		Description: Code identifying the country				

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Loop Hierarchical Level - Order

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
050	PRF	Purchase Order Reference	M	1		Must use
150	REF	Reference Identification	M	3		Must use
010		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	M	AN	1/12	Must use
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 170, Included: 1)						
<u>Code</u> <u>Name</u>						
O Order						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

PRF Purchase Order Reference

Pos: 050	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To provide reference to a specific purchase order

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PRF01	324	Purchase Order Number	M	AN	1/22	Must use
		Description: Identifying number for Purchase Order assigned by the orderer/purchaser				
PRF04	373	Date	O	DT	8/8	Used
		Description: Date expressed as CCYYMMDD				
		User Note 1: <i>PO Date</i>				

Semantics:

1. PRF04 is the date assigned by the purchaser to purchase order.

REF Reference Identification

Pos: 150	Max: 3
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1503, Included: 3)

Code Name

CO Customer Order Number

User Note 1:

Return if present on the order (850/860)

IA Internal Vendor Number

User Note 1:

Mandatory

Return value sent on the order (850/860)

IK Invoice Number

REF02	127	Reference Identification	M	AN	1/30	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

Loop Hierarchical Level - Pack

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
060	PO4	Item Physical Details	O	1		Used
190	MAN	Marks and Numbers	M	1		Must use
010		Loop HL	M		200000	Must use

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	M	AN	1/12	Must use
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 170, Included: 2)						
<u>Code</u> <u>Name</u>						
P Pack						
T Shipping Tare						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

PO4 Item Physical Details

Pos: 060	Max: 1
Detail - Optional	
Loop: HL	Elements: 3

User Option (Usage): Used

Purpose: To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO405	187	Weight Qualifier	C	ID	1/2	Used

Description: Code defining the type of weight

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

CodeList Summary (Total Codes: 51, Included: 1)

Code Name

G Gross Weight

PO406	384	Gross Weight per Pack	C	R	1/9	Used
-------	-----	-----------------------	---	---	-----	------

Description: Numeric value of gross weight per pack

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

PO407	355	Unit or Basis for Measurement Code	C	ID	2/2	Used
-------	-----	------------------------------------	---	----	-----	------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

User Note 1: *If WeightQualifier, Weight, or WeightUOM are present then all are required*

CodeList Summary (Total Codes: 794, Included: 1)

Code Name

LB Pound

Syntax Rules:

1. P0203 - If either PO402 or PO403 is present, then the other is required.
2. C0506 - If PO405 is present, then PO406 is required.
3. P0607 - If either PO406 or PO407 is present, then the other is required.
4. P0809 - If either PO408 or PO409 is present, then the other is required.
5. C1013 - If PO410 is present, then PO413 is required.
6. C1113 - If PO411 is present, then PO413 is required.
7. C1213 - If PO412 is present, then PO413 is required.
8. L13101112 - If PO413 is present, then at least one of PO410, PO411 or PO412 is required.
9. C1716 - If PO417 is present, then PO416 is required.
10. C1804 - If PO418 is present, then PO404 is required.

Semantics:

1. PO415 is used to indicate the relative layer of this package or range of packages within the layers of packaging. Relative Position 1 (value R1) is the innermost package.
2. PO416 is the package identifier or the beginning package identifier in a range of identifiers.
3. PO417 is the ending package identifier in a range of identifiers.
4. PO418 is the number of packages in this layer.

MAN Marks and Numbers

Pos: 190	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To indicate identifying marks and numbers for shipping containers

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
MAN01	88	Marks and Numbers Qualifier	M	ID	1/2	Must use

Description: Code specifying the application or source of Marks and Numbers (87)

User Note 1: *One of GM or CP must be provided*

CodeList Summary (Total Codes: 20, Included: 2)

Code Name

CP Carrier-Assigned Package ID Number

User Note 1:

Used with Parcel

GM SSCC-18 and Application Identifier

User Note 1:

Required for Direct to Warehouse/DC shipments

MAN02	87	Marks and Numbers	M	AN	1/48	Must use
-------	----	-------------------	---	----	------	----------

Description: Marks and numbers used to identify a shipment or parts of a shipment

Syntax Rules:

1. P0405 - If either MAN04 or MAN05 is present, then the other is required.
2. C0605 - If MAN06 is present, then MAN05 is required.

Semantics:

1. MAN01/MAN02 and MAN04/MAN05 may be used to identify two different marks and numbers assigned to the same physical container.
2. When both MAN02 and MAN03 are used, MAN02 is the starting number of a sequential range and MAN03 is the ending number of that range.
3. When both MAN05 and MAN06 are used, MAN05 is the starting number of a sequential range, and MAN06 is the ending number of that range.

Comments:

- 1.

Loop Hierarchical Level - Item

Pos: 010	Repeat: 200000
Mandatory	
Loop: HL	Elements: N/A

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
010	HL	Hierarchical Level	M	1		Must use
020	LIN	Item Identification	M	1		Must use
030	SN1	Item Detail (Shipment)	M	1		Must use
060	PO4	Item Physical Details	O	1		Used
070	PID	Product/Item Description	M	1		Must use
150	REF	Reference Identification	O	>1		Used
200	DTM	Date/Time Reference	O	2		Used
220		Loop N1	O		1	Used

HL Hierarchical Level

Pos: 010	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To identify dependencies among and the content of hierarchically related groups of data segments

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
HL01	628	Hierarchical ID Number	M	AN	1/12	Must use
Description: A unique number assigned by the sender to identify a particular data segment in a hierarchical structure						
HL02	734	Hierarchical Parent ID Number	M	AN	1/12	Must use
Description: Identification number of the next higher hierarchical data segment that the data segment being described is subordinate to						
HL03	735	Hierarchical Level Code	M	ID	1/2	Must use
Description: Code defining the characteristic of a level in a hierarchical structure						
CodeList Summary (Total Codes: 170, Included: 1)						
<u>Code</u> <u>Name</u>						
I Item						

Comments:

1. The HL segment is used to identify levels of detail information using a hierarchical structure, such as relating line-item data to shipment data, and packaging data to line-item data.
2. The HL segment defines a top-down/left-right ordered structure.
3. HL01 shall contain a unique alphanumeric number for each occurrence of the HL segment in the transaction set. For example, HL01 could be used to indicate the number of occurrences of the HL segment, in which case the value of HL01 would be "1" for the initial HL segment and would be incremented by one in each subsequent HL segment within the transaction.
4. HL02 identifies the hierarchical ID number of the HL segment to which the current HL segment is subordinate.
5. HL03 indicates the context of the series of segments following the current HL segment up to the next occurrence of an HL segment in the transaction. For example, HL03 is used to indicate that subsequent segments in the HL loop form a logical grouping of data referring to shipment, order, or item-level information.
6. HL04 indicates whether or not there are subordinate (or child) HL segments related to the current HL segment.

LIN Item Identification

Pos: 020	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 7

User Option (Usage): Must use

Purpose: To specify basic item identification data

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
LIN01	350	Assigned Identification	M	AN	1/20	Must use

Description: Alphanumeric characters assigned for differentiation within a transaction set

User Note 1: Must match value sent on the Order (850/860)

LIN02	235	Product/Service ID Qualifier	X	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 1)

Code Name

BP Buyer's Part Number

LIN03	234	Product/Service ID	C	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

Description: Identifying number for a product or service

User Note 1:

Conditionally required when sent on the PO (EDI 850)

LIN04	235	Product/Service ID Qualifier	X	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 2)

Code Name

MG Manufacturer's Part Number

VC Vendor's (Seller's) Catalog Number

LIN05	234	Product/Service ID	X	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

Description: Identifying number for a product or service

LIN06	235	Product/Service ID Qualifier	X	ID	2/2	Used
-------	-----	------------------------------	---	----	-----	------

Description: Code identifying the type/source of the descriptive number used in Product/Service ID (234)

CodeList Summary (Total Codes: 477, Included: 2)

Code Name

MG Manufacturer's Part Number

VC Vendor's (Seller's) Catalog Number

LIN07	234	Product/Service ID	X	AN	1/48	Used
-------	-----	--------------------	---	----	------	------

Description: Identifying number for a product or service

Syntax Rules:

1. P0405 - If either LIN04 or LIN05 is present, then the other is required.
2. P0607 - If either LIN06 or LIN07 is present, then the other is required.
3. P0809 - If either LIN08 or LIN09 is present, then the other is required.
4. P1011 - If either LIN10 or LIN11 is present, then the other is required.
5. P1213 - If either LIN12 or LIN13 is present, then the other is required.
6. P1415 - If either LIN14 or LIN15 is present, then the other is required.
7. P1617 - If either LIN16 or LIN17 is present, then the other is required.
8. P1819 - If either LIN18 or LIN19 is present, then the other is required.
9. P2021 - If either LIN20 or LIN21 is present, then the other is required.
10. P2223 - If either LIN22 or LIN23 is present, then the other is required.
11. P2425 - If either LIN24 or LIN25 is present, then the other is required.
12. P2627 - If either LIN26 or LIN27 is present, then the other is required.
13. P2829 - If either LIN28 or LIN29 is present, then the other is required.
14. P3031 - If either LIN30 or LIN31 is present, then the other is required.

Semantics:

1. LIN01 is the line item identification

SN1 Item Detail (Shipment)

Pos: 030	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 2

User Option (Usage): Must use

Purpose: To specify line-item detail relative to shipment

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SN102	382	Number of Units Shipped	M	R	1/10	Must use

Description: Numeric value of units shipped in manufacturer's shipping units for a line item or transaction set

SN103	355	Unit or Basis for Measurement Code	M	ID	2/2	Must use
-------	-----	------------------------------------	---	----	-----	----------

Description: Code specifying the units in which a value is being expressed, or manner in which a measurement has been taken

CodeList Summary (Total Codes: 794, Included: 210)

<u>Code</u>	<u>Name</u>
AS	Assortment
AY	Assembly
B1	Box
BA	Bale
BB	Base Box
BC	Bucket
BD	Bundle
BE	Blade
BF	Board Feet
BG	Bag
BH	Brush
BI	Bar
BJ	Band
BK	Book
BL	Block
BN	Bulk
BO	Bottle
BR	Barrel
BT	Belt
BU	Bushel
BX	Box
C4	Carload
CA	Case
CB	Carboy
CC	Cubic Centimeter
CD	Carat
CE	Centigrade, Celsius
CF	Cubic Feet
CG	Card
CH	Container

<u>Code</u>	<u>Name</u>
CI	Cubic Inches
CJ	Cone
CK	Connector
CL	Cylinder
CM	Centimeter
CN	Can
CO	Coil
CP	Crate
CQ	Cartridge
CR	Cubic Meter
CS	Cassette
CT	Carton
CU	Cup
CV	Cover
CW	Hundred Pounds (CWT)
CX	Cost
CY	Cubic Yard
CZ	Combo
DA	Days
DC	Decigram
DE	Deal
DI	Disc
DK	Kilometers
DL	Deciliter
DM	Decimeter
DN	Dozen
DO	Dollars, U.S.
DP	Dispenser
DR	Drum
DS	Display
DZ	Dozen
EA	Each
EP	Eleven pack
EV	Envelope
F2	Square Foot
FA	Fahrenheit
FO	Fluid Ounce
FP	Pounds per Sq. Ft.
FT	Foot
GA	Gallon
GI	Imperial Gallons
GL	Gallon
GM	Grams per Sq. Meter
GR	Gram
GS	Gross
GY	Gross Yard
HA	Hank 100ft of rope

<u>Code</u>	<u>Name</u>
HC	Hundred Count
HD	Half Dozen
HG	Hectogram
HR	Hours
HU	Hundred
IC	Increment
IN	Inch
JB	Jumbo
JG	Jug
JO	Joint
JR	Jar
JU	Jug
KA	Can
KE	Keg
KG	Kilogram
KH	Kilowatt Hour
KI	Kit
KT	Kit
KV	Kelvin
KW	Kilograms per Millimeter
LB	Pound
LC	Linear Centimeter
LF	Linear Foot
LG	Log
LH	Labor Hours
LI	Linear Inch
LK	Link
LM	Linear Meter
LN	Length
LO	Lot
LP	Pounds per Cubic Inch
LR	Layer(s)
LS	Lump Sum
LT	Liter
LY	Linear Yard
MA	Machine/Unit
MB	Minimum Buying Unit
MC	Master Case
ME	Milligram
MF	Milligram per Sq. Ft. per Side
MG	Metric Gross Ton
MI	Milligrams Per Sq Inch
ML	Milliliter
MM	Millimeter
MN	Metric Net Ton
MO	Months
MR	Meter

<u>Code</u>	<u>Name</u>
MS	Square Millimeter
MT	Metric Long Ton
MU	Minutes
MV	Monetary Value
MX	Mixed
NB	Barge
NC	Car
NL	Load
NN	Train
NR	Container
NT	Trailer
NV	Vehicle
OP	Two pack
OZ	Ounce - Av
P1	Each
P3	Three pack
P4	Four-pack
P5	Five-pack
P6	Six pack
P7	Seven pack
P8	Eight-pack
P9	Nine pack
PA	Pail
PC	Piece
PD	Pad
PE	Pounds Equivalent
PF	Pallet (Lift)
PG	Pounds Gross
PH	Pack (PAK)
PI	Pounds Per Inch of Length
PK	Pack
PL	Pallet/Unit Load
PN	Pounds Net
PP	Plate
PR	Pair
PS	Pounds per Sq. Inch
PT	Pint
PW	Pounds per Inch of Width
QD	Quarter Dozen
QR	Quire
QT	Quart
RD	Rod
RE	Reel
RL	Roll
RM	Ream
RO	Roll
SA	Sandwich

<u>Code</u>	<u>Name</u>
SC	Square Centimeter
SE	Section
SF	Square Foot
SG	Segment
SH	Sheet
SI	Square Inch
SJ	Sack
SK	Skid/Pallet
SL	Sleeve
SM	Square Meter
SO	Spool
SP	Shelf Package
SQ	Square
SR	Strip
ST	Set
SX	Shipment
SY	Square Yard
TB	Tube
TC	Truckload
TE	Tote
TG	Gross Ton
TH	Thousand
TK	Tank
TN	Net Ton (2,000 LB).
TO	Troy Ounce
TP	Ten-pack
TS	Short Ton (2000 Lbs.)
TU	Thousand Linear Yards
TW	Thousand Pieces
TY	Tray
UN	Unit
VP	Vendor Price
WH	Wheel
WI	Wiper
WK	Week
WR	Wrap
YD	Yard
YR	Years
ZP	Each

Syntax Rules:

1. P0506 - If either SN105 or SN106 is present, then the other is required.

Semantics:

1. SN101 is the ship notice line-item identification.

Comments:

1. SN103 defines the unit of measurement for both SN102 and SN104.

PO4 Item Physical Details

Pos: 060	Max: 1
Detail - Optional	
Loop: HL	Elements: 1

User Option (Usage): Used

Purpose: To specify the physical qualities, packaging, weights, and dimensions relating to the item

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PO401	356	Pack	O	N0	1/6	Used

Description: The number of inner containers, or number of eaches if there are no inner containers, per outer container

Syntax Rules:

1. P0203 - If either PO402 or PO403 is present, then the other is required.
2. C0506 - If PO405 is present, then PO406 is required.
3. P0607 - If either PO406 or PO407 is present, then the other is required.
4. P0809 - If either PO408 or PO409 is present, then the other is required.
5. C1013 - If PO410 is present, then PO413 is required.
6. C1113 - If PO411 is present, then PO413 is required.
7. C1213 - If PO412 is present, then PO413 is required.
8. L13101112 - If PO413 is present, then at least one of PO410, PO411 or PO412 is required.
9. C1716 - If PO417 is present, then PO416 is required.
10. C1804 - If PO418 is present, then PO404 is required.

Semantics:

1. PO415 is used to indicate the relative layer of this package or range of packages within the layers of packaging. Relative Position 1 (value R1) is the innermost package.
2. PO416 is the package identifier or the beginning package identifier in a range of identifiers.
3. PO417 is the ending package identifier in a range of identifiers.
4. PO418 is the number of packages in this layer.

PID Product/Item Description

Pos: 070	Max: 1
Detail - Mandatory	
Loop: HL	Elements: 3

User Option (Usage): Must use

Purpose: To describe a product or process in coded or free-form format

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
PID01	349	Item Description Type	M	ID	1/1	Must use

Description: Code indicating the format of a description

CodeList Summary (Total Codes: 3, Included: 1)

Code Name

F Free-form

PID02	750	Product/Process Characteristic Code	M	ID	2/3	Must use
-------	-----	-------------------------------------	---	----	-----	----------

Description: Code identifying the general class of a product or process characteristic

CodeList Summary (Total Codes: 217, Included: 1)

Code Name

08 Product

PID05	352	Description	M	AN	1/80	Must use
-------	-----	-------------	---	----	------	----------

Description: A free-form description to clarify the related data elements and their content

Syntax Rules:

1. C0403 - If PID04 is present, then PID03 is required.
2. R0405 - At least one of PID04 or PID05 is required.
3. C0703 - If PID07 is present, then PID03 is required.
4. C0804 - If PID08 is present, then PID04 is required.
5. C0905 - If PID09 is present, then PID05 is required.

Semantics:

1. Use PID03 to indicate the organization that publishes the code list being referred to.
2. PID04 should be used for industry-specific product description codes.
3. PID08 describes the physical characteristics of the product identified in PID04. A "Y" indicates that the specified attribute applies to this item; an "N" indicates it does not apply. Any other value is indeterminate.
4. PID09 is used to identify the language being used in PID05.

REF Reference Identification

Pos: 150	Max: >1
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To specify identifying information

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
REF01	128	Reference Identification Qualifier	M	ID	2/3	Must use

Description: Code qualifying the Reference Identification

CodeList Summary (Total Codes: 1503, Included: 2)

Code Name

LT Lot Number

SE Serial Number

REF02	127	Reference Identification	M	AN	1/30	Must use
-------	-----	--------------------------	---	----	------	----------

Description: Reference information as defined for a particular Transaction Set or as specified by the Reference Identification Qualifier

Syntax Rules:

1. R0203 - At least one of REF02 or REF03 is required.

Semantics:

1. REF04 contains data relating to the value cited in REF02.

DTM Date/Time Reference

Pos: 200	Max: 2
Detail - Optional	
Loop: HL	Elements: 2

User Option (Usage): Used

Purpose: To specify pertinent dates and times

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
DTM01	374	Date/Time Qualifier	M	ID	3/3	Must use

Description: Code specifying type of date or time, or both date and time

CodeList Summary (Total Codes: 1112, Included: 2)

Code Name

405 Production

511 Expiration

DTM02	373	Date	M	DT	8/8	Must use
-------	-----	------	---	----	-----	----------

Description: Date expressed as CCYYMMDD

Syntax Rules:

1. R020305 - At least one of DTM02, DTM03 or DTM05 is required.
2. C0403 - If DTM04 is present, then DTM03 is required.
3. P0506 - If either DTM05 or DTM06 is present, then the other is required.

Loop Name

Pos: 220	Repeat: 1
Optional	
Loop: N1	Elements: N/A

User Option (Usage): Used

Purpose: To identify a party by type of organization, name, and code

Loop Summary:

<u>Pos</u>	<u>Id</u>	<u>Segment Name</u>	<u>Req</u>	<u>Max Use</u>	<u>Repeat</u>	<u>Usage</u>
220	N1	Name	M	1		Must use
250	N4	Geographic Location	M	1		Must use

N1 Name

Pos: 220	Max: 1
Detail - Mandatory	
Loop: N1	Elements: 2

User Option (Usage): Must use

Purpose: To identify a party by type of organization, name, and code

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N101	98	Entity Identifier Code	M	ID	2/3	Must use

Description: Code identifying an organizational entity, a physical location, property or an individual

CodeList Summary (Total Codes: 1312, Included: 1)

Code Name

CT Country of Origin

N102	93	Name	M	AN	1/60	Must use
------	----	------	---	----	------	----------

Description: Free-form name

Syntax Rules:

1. R0203 - At least one of N102 or N103 is required.
2. P0304 - If either N103 or N104 is present, then the other is required.

Comments:

1. This segment, used alone, provides the most efficient method of providing organizational identification. To obtain this efficiency the "ID Code" (N104) must provide a key to the table maintained by the transaction processing party.
2. N105 and N106 further define the type of entity in N101.

N4 Geographic Location

Pos: 250	Max: 1
Detail - Mandatory	
Loop: N1	Elements: 1

User Option (Usage): Must use

Purpose: To specify the geographic place of the named party

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
N404	26	Country Code	M	ID	2/3	Must use

Description: Code identifying the country

Syntax Rules:

1. C0605 - If N406 is present, then N405 is required.

Comments:

1. A combination of either N401 through N404, or N405 and N406 may be adequate to specify a location.
2. N402 is required only if city name (N401) is in the U.S. or Canada.

CTT Transaction Totals

Pos: 010	Max: 1
Summary - Optional	
Loop: N/A	Elements: 1

User Option (Usage): Used

Purpose: To transmit a hash total for a specific element in the transaction set

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
CTT01	354	Number of Line Items	M	N0	1/6	Must use

Description: Total number of line items in the transaction set

Syntax Rules:

1. P0304 - If either CTT03 or CTT04 is present, then the other is required.
2. P0506 - If either CTT05 or CTT06 is present, then the other is required.

Comments:

- 1.

SE Transaction Set Trailer

Pos: 020	Max: 1
Summary - Mandatory	
Loop: N/A	Elements: 2

User Option (Usage): Must use

Purpose: To indicate the end of the transaction set and provide the count of the transmitted segments (including the beginning (ST) and ending (SE) segments)

Element Summary:

<u>Ref</u>	<u>Id</u>	<u>Element Name</u>	<u>Req</u>	<u>Type</u>	<u>Min/Max</u>	<u>Usage</u>
SE01	96	Number of Included Segments	M	N0	1/10	Must use
		Description: Total number of segments included in a transaction set including ST and SE segments				
SE02	329	Transaction Set Control Number	M	AN	4/9	Must use
		Description: Identifying control number that must be unique within the transaction set functional group assigned by the originator for a transaction set				

Comments:

1. SE is the last segment of each transaction set.